

specter

SPSS MODULES
SNOOT PENDANT 50

bold
lighting



SNOOT PENDANT 50


Our Magnetic track system, SPECTER, is a highly configurable, 2 circuits, 24VDC low voltage track system. Thanks to its magnet mounting technology, the modules are inter-changeable instantaneously. Our track is available in ceiling pendant, surface and recessed mounting for both ceiling and walls. SPECTER track is also available with an optional linear uplight feature. The snoot pendant module complements the SPECTER range with a minimalistic pendant cylinder equipped with a wide range of optics and optical accessories allowing professional lighting.

- ☐ Up to 1,300lm delivered output
- ☐ Available in 2 diameter sizes, 1.5" and 2"
- ☐ Various optical accessories available such as beam shaping lenses, Honeycomb louvers or barndoors
- ☐ Beam options, narrow, medium, flood and wide
- ☐ Fixtures designed to mount in SPECTER track
- ☐ Available in 4 standard finishes: Black, white, silver and bronze

Notes: ¹ Available dimming 0-10V and DALI

Code example: **SPSF-P**20W-W-N827-2

STANDARD FINISHES



Z

B

S

W

DELIVERED LUMEN OUTPUT

Length		Watts		CRI +80				CRI +90			
				2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
2"	10W			785lm	872lm	959lm	1055lm	633lm	703lm	773lm	851lm


Series		Length		Body Finish		Baffle Finish		Beam Angle		CRI		Color Temp		Circuit	
SPSF-P	20	2"	W	White	W	White	N	12°	8	+80	27	2700K	1	1-Circuit	
			B	Black	B	Black	M	24°	9	+90	30	3000K	2	2-Circuit	
			S	Silver	S	Silver	F	36°			35	3500K			
			Z	Bronze	Z	Bronze	H	50°			40	4000K			
			X	Custom	X	Custom									




Bold Lighting
4710 Ecton Dr., Marietta, GA 30066, USA
info@boldlighting.us www.boldlighting.us
t: +1-678-903-4061

Photometric data:
Type C Polar Curves


12° Beam Angle




24° Beam Angle



36° Beam Angle



50° Beam Angle



SNOOT PENDANT 50

