

Light efficiency:

73 Lumen/Watt

Light quality:

CRI: 79.8

Color temperature:

2931 K

Output: 3756 lm

Peak: 5069 cd

Power: 51.1 W

PF: 1.0



Beam angle


52.5°

Product name:

608RA-6-XTM19-50LM-30K-83-  
DA60-UNV-DIM10-MC-S


Date and time:

12/5/2017 8:20:10 AM





CIE 1931  
x: 0.446  
y: 0.413


Spectra




## Color details



TM30: 77.9



CRI: 79.8 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
77.5	85.2	93.0	80.0	76.8	80.7	84.4	60.7	6.9	66.6	78.6	63.7	78.5	95.7	70.4

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
76.1	76.4	68.2	72.8	80.4	83.0	70.1	84.6	79.8	79.0	77.3	79.5	86.3	82.4	75.2	79.3

## Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	x	y	u	v	Δuv
2931 K	79.8	6.9	77.9	98.7	0.446	0.413	0.252	0.351	0.0024

## TM30 details







**Rf 77.9**

Fidelity index Rf


**Rg 98.7**

Gamut index Rg

Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	76	-11%	-4%
2	76	-9%	8%
3	68	-3%	15%
4	73	8%	14%
5	80	12%	8%
6	83	9%	-4%
7	70	5%	-16%
8	85	-2%	-9%
9	80	-8%	-7%
10	79	-11%	1%
11	77	-8%	11%
12	80	3%	8%
13	86	8%	-1%
14	82	7%	-10%
15	75	3%	-13%
16	79	-8%	-12%



## Beam details



### Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
5069lx	1267lx	563lx	317lx	203lx	141lx	103lx	79lx	63lx	51lx	42lx	35lx	30lx	26lx	23lx	20lx	18lx	16lx	14lx	13lx
471fcd	117.7fcd	52.3fcd	29.4fcd	18.8fcd	13.1fcd	9.6fcd	7.4fcd	5.8fcd	4.7fcd	3.9fcd	3.3fcd	2.8fcd	2.4fcd	2.1fcd	1.8fcd	1.6fcd	1.5fcd	1.3fcd	1.2fcd

### Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5069	5069	4969	4838	4682	4464	4247	4004	3754	3503	3250	2996	2775	2560	2352	2157	1962	1571	1162	806
100%	100%	98%	95%	92%	88%	84%	79%	74%	69%	64%	59%	55%	50%	46%	43%	39%	31%	23%	16%

### Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5069	5069	4969	4838	4682	4464	4247	4004	3754	3503	3250	2996	2775	2560	2352	2157	1962	1571	1162	806
100%	100%	98%	95%	92%	88%	84%	79%	74%	69%	64%	59%	55%	50%	46%	43%	39%	31%	23%	16%

### Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5069	5069	4969	4838	4682	4464	4247	4004	3754	3503	3250	2996	2775	2560	2352	2157	1962	1571	1162	806
100%	100%	98%	95%	92%	88%	84%	79%	74%	69%	64%	59%	55%	50%	46%	43%	39%	31%	23%	16%

### Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5069	5069	4969	4838	4682	4464	4247	4004	3754	3503	3250	2996	2775	2560	2352	2157	1962	1571	1162	806
100%	100%	98%	95%	92%	88%	84%	79%	74%	69%	64%	59%	55%	50%	46%	43%	39%	31%	23%	16%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
52.5°	80.2°	93°	99.8%	98.1%