

PHILIPS DAY-BRITE PHOTOMETRIC
938 S. GREEN ST.
TUPELO, MS 38804
NVLAP CODE: 200016-0

Test Report Number: FO38709
Test Item Number: LED COMPAC 1-3V

Report Number	FO38709
Test Item	LED COMPAC 1-3V LGIT H35C4 LED @550mA
Product Type	
Test Purpose	
Sales Order Reference	
Works Order Number	
Test Item Reference	LED COMPAC
Lab Test Method Reference	LM79-08
Test Standards	
Lab Location Reference	TUPELO
Tested by	MARY MOSES
Date of Test	11/11/17
Number of products Tested	
Analysed By	
Authorised Date	

SUPRAH SINGH/KJ

PHILIPS DAY-BRITE PHOTOMETRIC
938 S. GREEN ST.
TUPELO, MS 38804
NVLAP CODE: 200016-0

Test Report Number: FO38709
Test Item Number: LED COMPAC 1-3V

Product Name	LED COMPAC 1-3V LGIT H35C4 LED
Part / Serial Number	
Type of Product	
Base Type	
Driver Type	DC POWER SUPPLY
Operating Orientation	
Test Orientation	
Manufacturer	
Date of Manufacture	
Thermal Management	
Dimmable	

Test Time (minutes)	Ambient Temperature (deg C)	Relative Humidity (%RH)	Pre-burning Time (hours)	Stabilisation Time (minutes)
0.00	24.50	0.00	0.00	0.00

Photometric Measurements

Total Luminous Flux (lm)	Electrical Power (W)	Luminous Efficacy (lm/W)	Test Distance (m)
220.8	1.70	129.90	6.82


Electrical Measurements

Power Factor	Power (W)	Voltage (V)	Current (A)	Apparent Power (VA)	Frequency (Hz)	Current THD (%)	Voltage THD (%)
0.00	1.70	2.92	0.55	0.00	0.00	0.00	0.00

Test Report Number: FO38709
Test Item Number: LED COMPAC 1-3V

Zonal Lumen Summary

	Summary Zonal Lumens	Zonal Lumens - % Lamp	Zonal Lumens - % Fixture
0 to 30	180.23	81.61	81.61
0 to 40	188.22	85.23	85.23
0 to 60	203.11	91.98	91.98
0 to 90	220.20	99.71	99.71
40 to 90	31.98	14.48	14.48
60 to 90	17.09	7.74	7.74
90 to 180	0.64	0.29	0.29
0 to 180	220.83	100.00	100.00




PHILIPS DAY-BRITE PHOTOMETRIC
 938 S. GREEN ST.
 TUPELO, MS 38804
 NVLAP CODE: 200016-0

Test Report Number: FO38709
 Test Item Number: LED COMPAC 1-3V

Luminaire Dimensions

Sample Diameter/ Length (mm)	Sample Width (mm)	Sample Height/ Depth (mm)	Luminous Diameter/ Length (mm)	Luminous Width (mm)	Luminous Height/ Depth (mm)	Luminous C0-plane (mm)	Luminous C90-plane (mm)	Luminous C180-plane (mm)	Luminous C270-plane (mm)
-50.90	-50.90	0.00	-51.82	-51.82	0.00	0.00	0.00	0.00	0.00





Minimum Intensity (cd)	Maximum Intensity (cd)
0.00	0.00

PHILIPS DAY-BRITE PHOTOMETRIC
938 S. GREEN ST.
TUPELO, MS 38804
NVLAP CODE: 200016-0

Test Report Number: FO38709
Test Item Number: LED COMPAC 1-3V


Polar Plot (cd)



PHILIPS DAY-BRITE PHOTOMETRIC
 938 S. GREEN ST.
 TUPELO, MS 38804
 NVLAP CODE: 200016-0

Test Report Number: FO38709
 Test Item Number: LED COMPAC 1-3V

Illuminance at a Distance



Target % of Peak Intensity	Beam Angle to % Intensity Value (degrees)	Beam Angle to Specified % Intensity Value (degrees) [-]
50.00	22.51	22.51

Beam Spread (at 50% Max CD)		Field Spread (at 10% Max CD)	
(deg) Horiz	(deg) Vert	(deg) Horiz	(deg) Vert
NaN	NaN	NaN	NaN

Total Luminous Flux	Field (%)	Field Flux (lm)	Beam Flux (%)	Beam Flux (lm)	Beam Spill (%)
NaN	NaN	0.00	NaN	0.00	NaN

PHILIPS DAY-BRITE PHOTOMETRIC
938 S. GREEN ST.
TUPELO, MS 38804
NVLAP CODE: 200016-0

Test Report Number: FO38709
Test Item Number: LED COMPAC 1-3V

Candela Table (cd)

	0.0	22.5	45.0	67.5	90.0	112.5	135.0	157.5	180.0	202.5	225.0	247.5	270.0	292.5	315.0	337.5
0.0	1068.0	1068.0	1068.0	1068.0	1068.0	1068.0	1068.0	1068.0	1068.0	1068.0	1068.0	1068.0	1068.0	1068.0	1068.0	1068.0
2.5	1033.2	1033.2	1033.2	1033.2	1033.2	1033.2	1033.2	1033.2	1033.2	1033.2	1033.2	1033.2	1033.2	1033.2	1033.2	1033.2
5.0	937.6	937.6	937.6	937.6	937.6	937.6	937.6	937.6	937.6	937.6	937.6	937.6	937.6	937.6	937.6	937.6
7.5	799.3	799.3	799.3	799.3	799.3	799.3	799.3	799.3	799.3	799.3	799.3	799.3	799.3	799.3	799.3	799.3
10.0	626.5	626.5	626.5	626.5	626.5	626.5	626.5	626.5	626.5	626.5	626.5	626.5	626.5	626.5	626.5	626.5
12.5	442.1	442.1	442.1	442.1	442.1	442.1	442.1	442.1	442.1	442.1	442.1	442.1	442.1	442.1	442.1	442.1
15.0	289.1	289.1	289.1	289.1	289.1	289.1	289.1	289.1	289.1	289.1	289.1	289.1	289.1	289.1	289.1	289.1
17.5	180.0	180.0	180.0	180.0	180.0	180.0	180.0	180.0	180.0	180.0	180.0	180.0	180.0	180.0	180.0	180.0
20.0	105.0	105.0	105.0	105.0	105.0	105.0	105.0	105.0	105.0	105.0	105.0	105.0	105.0	105.0	105.0	105.0
22.5	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6
25.0	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7
27.5	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1	22.1
30.0	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8
32.5	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0
35.0	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4	12.4
37.5	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3	11.3
40.0	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7
42.5	10.2	10.2	10.2	10.2	10.2	10.2	10.2	10.2	10.2	10.2	10.2	10.2	10.2	10.2	10.2	10.2
45.0	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9
47.5	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6
50.0	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.1
52.5	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6	8.6
55.0	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1
57.5	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6	7.6
60.0	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1
62.5	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.7
65.0	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3
67.5	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0
70.0	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7
72.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5
75.0	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3
77.5	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
80.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
82.5	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9
85.0	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8
87.5	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7
90.0	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
92.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
97.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
102.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
107.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
112.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
117.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
122.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
127.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
132.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

PHILIPS DAY-BRITE PHOTOMETRIC
938 S. GREEN ST.
TUPELO, MS 38804
NVLAP CODE: 200016-0

Test Report Number: FO38709
Test Item Number: LED COMPAC 1-3V

Candela Table (cd)

	360.0
0.0	1068.0
2.5	1033.2
5.0	937.6
7.5	799.3
10.0	626.5
12.5	442.1
15.0	289.1
17.5	180.0
20.0	105.0
22.5	58.6
25.0	33.7
27.5	22.1
30.0	16.8
32.5	14.0
35.0	12.4
37.5	11.3
40.0	10.7
42.5	10.2
45.0	9.9
47.5	9.6
50.0	9.1
52.5	8.6
55.0	8.1
57.5	7.6
60.0	7.1
62.5	6.7
65.0	6.3
67.5	6.0
70.0	5.7
72.5	5.5
75.0	5.3
77.5	5.1
80.0	5.0
82.5	4.9
85.0	4.8
87.5	4.7
90.0	4.6
92.5	0.0
95.0	0.0
97.5	0.0
100.0	0.0
102.5	0.0
105.0	0.0
107.5	0.0
110.0	0.0
112.5	0.0
115.0	0.0
117.5	0.0
120.0	0.0
122.5	0.0
125.0	0.0
127.5	0.0
130.0	0.0
132.5	0.0

PHILIPS DAY-BRITE PHOTOMETRIC
938 S. GREEN ST.
TUPELO, MS 38804
NVLAP CODE: 200016-0

Test Report Number: FO38709
Test Item Number: LED COMPAC 1-3V

Candela Table (cd)

	0.0	22.5	45.0	67.5	90.0	112.5	135.0	157.5	180.0	202.5	225.0	247.5	270.0	292.5	315.0	337.5
135.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
137.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
142.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
147.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
152.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
157.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
162.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
167.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
172.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
177.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

PHILIPS DAY-BRITE PHOTOMETRIC
938 S. GREEN ST.
TUPELO, MS 38804
NVLAP CODE: 200016-0

Test Report Number: FO38709
Test Item Number: LED COMPAC 1-3V

Candela Table (cd)

	360.0
135.0	0.0
137.5	0.0
140.0	0.0
142.5	0.0
145.0	0.0
147.5	0.0
150.0	0.0
152.5	0.0
155.0	0.0
157.5	0.0
160.0	0.0
162.5	0.0
165.0	0.0
167.5	0.0
170.0	0.0
172.5	0.0
175.0	0.0
177.5	0.0
180.0	0.0