

Light efficiency:

105 Lumen/Watt

Light quality:

CRI: 83.2

Color temperature:

2996 K

Output: 8056 lm

Peak: 24967 cd

Power: 76.5 W

PF: 0.99




Product name:

680XK-9-CXB-80LM-30K-80-SA30-10V-MC-S-M16


Date and time:

1/25/2018 2:55:25 PM




CIE 1931
x: 0.439
y: 0.407



Spectra




Power




Color details



TM30: 82.9



CRI: 83.2 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
81.7	90.8	97.1	81.2	81.1	88.3	84.1	61.2	11.2	78.0	80.0	66.7	83.9	98.7	74.0


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
78.0	80.1	77.2	88.8	90.5	93.4	86.3	91.5	85.7	77.7	77.3	83.2	87.2	78.6	78.1	75.1

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
78.9	94.9	81.8	78.1	81.5	82.7	83.3	86.5	96.1	89.5	86.6	84.6	83.5	72.4	74.6

CQS: 82.4



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2996 K	83.2	11.2	82.9	95.4	82.4	0.439	0.407	0.251	0.349	0.0009

TM30 details







Rf 82.9

Fidelity index Rf


Rg 95.4

Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	78	-11%	0%
2	80	-8%	6%
3	77	-3%	10%
4	89	0%	6%
5	90	-1%	4%
6	93	2%	-2%
7	86	-5%	-5%
8	92	-4%	0%
9	86	-6%	5%
10	78	-4%	12%
11	77	1%	15%
12	83	7%	4%
13	87	5%	-6%
14	79	5%	-14%
15	78	-3%	-12%
16	75	-7%	-16%



Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
24967lx	6242lx	2774lx	1560lx	999lx	694lx	510lx	390lx	308lx	250lx	206lx	173lx	148lx	127lx	111lx	98lx	86lx	77lx	69lx	62lx
2319.5fcd	579.9fcd	257.7fcd	145fcd	92.8fcd	64.4fcd	47.3fcd	36.2fcd	28.6fcd	23.2fcd	19.2fcd	16.1fcd	13.7fcd	11.8fcd	10.3fcd	9.1fcd	8fcd	7.2fcd	6.4fcd	5.8fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
25.0K	25.0K	23.5K	21.5K	19.3K	16.9K	14.4K	12.4K	10.6K	8.9K	7.7K	6.5K	5.6K	4.8K	3.9K	2.8K	1.6K	1.0K	0.5K	0.1K
100%	100%	94%	86%	77%	68%	58%	50%	42%	36%	31%	26%	22%	19%	16%	11%	7%	4%	2%	1%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
25.0K	25.0K	23.5K	21.5K	19.3K	16.9K	14.4K	12.4K	10.6K	8.9K	7.7K	6.5K	5.6K	4.8K	3.9K	2.8K	1.6K	1.0K	0.5K	0.1K
100%	100%	94%	86%	77%	68%	58%	50%	42%	36%	31%	26%	22%	19%	16%	11%	7%	4%	2%	1%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
25.0K	25.0K	23.5K	21.5K	19.3K	16.9K	14.4K	12.4K	10.6K	8.9K	7.7K	6.5K	5.6K	4.8K	3.9K	2.8K	1.6K	1.0K	0.5K	0.1K
100%	100%	94%	86%	77%	68%	58%	50%	42%	36%	31%	26%	22%	19%	16%	11%	7%	4%	2%	1%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
25.0K	25.0K	23.5K	21.5K	19.3K	16.9K	14.4K	12.4K	10.6K	8.9K	7.7K	6.5K	5.6K	4.8K	3.9K	2.8K	1.6K	1.0K	0.5K	0.1K
100%	100%	94%	86%	77%	68%	58%	50%	42%	36%	31%	26%	22%	19%	16%	11%	7%	4%	2%	1%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
27.9°	61°	71.1°	99.8%	99.5%