



IES INDOOR REPORT

PHOTOMETRIC FILENAME : BIO-STD-FLSH-LED4-SO-AWL-D1W.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TEST] L021507501R01
 [TESTLAB] LIGHT LABORATORY, INC.
 [ISSUE DATE] 3/4/2015
 [MANUFACT] PRUDENTIAL LTG.
 [LUMCAT] BIO-STD-FLSH-LED4-SO-AWL-D1W
 [LUMINAIRE] 4-1/2"L. X 48"W. X 5"H. LED LUMINAIRE
 [MORE] PRISMATIC LENS
 [BALLASTCAT] OSRAM OPTOTRONIC
 [BALLAST] INPUT: 120-277VAC
 [LAMPPOSITION] 0,0
 [LAMPCAT] N/A
 [OTHER] INDICATING THE CANDELA VALUES ARE ABSOLUTE AND
 [MORE] SHOULD NOT BE FACTORED FOR DIFFERENT LAMP RATINGS.
 [INPUT] 120VAC
 [TEST PROCEDURE] IESNA:LM-79-08

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	3763
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	96
Total Luminaire Watts	39
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.58
Spacing Criterion (90-270)	1.08
Spacing Criterion (Diagonal)	1.32
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.33 ft
Luminous Width (90-270)	3.94 ft
Luminous Height	0.00 ft

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BIO-STD-FLSH-LED4-SO-AWL-D1W.IES

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	13681	15667	8274
55	10665	11688	7689
65	8668	9004	6606
75	6596	6527	5428
85	3673	3877	3264

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BIO-STD-FLSH-LED4-SO-AWL-D1W.IES

CANDELA TABULATION

	0	5	10	15	20	25	30	35	40	45
0	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30
5	2023.15	2018.85	2014.55	2003.80	1993.05	1978.00	1960.80	1937.15	1911.35	1879.10
10	2322.00	2322.00	2315.55	2300.50	2285.45	2268.25	2244.60	2214.50	2177.95	2137.10
15	2681.05	2672.45	2657.40	2627.30	2588.60	2543.45	2498.30	2446.70	2390.80	2334.90
20	2777.80	2779.95	2786.40	2805.75	2822.95	2825.10	2805.75	2760.60	2683.20	2580.00
25	2279.00	2287.60	2304.80	2343.50	2395.10	2463.90	2541.30	2631.60	2709.00	2732.65
30	1915.65	1917.80	1926.40	1943.60	1975.85	2021.00	2081.20	2177.95	2300.50	2433.80
35	1668.40	1666.25	1672.70	1683.45	1700.65	1722.15	1750.10	1801.70	1881.25	2005.95
40	1419.00	1419.00	1425.45	1431.90	1451.25	1468.45	1489.95	1522.20	1567.35	1638.30
45	1169.60	1171.75	1176.05	1182.50	1191.10	1210.45	1231.95	1257.75	1290.00	1339.45
50	922.35	924.50	926.65	935.25	941.70	956.75	973.95	997.60	1027.70	1066.40
55	739.60	737.45	737.45	739.60	741.75	746.05	754.65	765.40	782.60	810.55
60	589.10	586.95	589.10	589.10	591.25	595.55	597.70	602.00	608.45	619.20
65	442.90	442.90	442.90	442.90	445.05	447.20	449.35	451.50	455.80	460.10
70	318.20	318.20	318.20	318.20	318.20	318.20	318.20	318.20	318.20	318.20
75	206.40	206.40	206.40	208.55	208.55	208.55	208.55	206.40	206.40	204.25
80	107.50	109.65	109.65	109.65	111.80	113.95	113.95	111.80	111.80	109.65
85	38.70	38.70	38.70	40.85	40.85	40.85	40.85	40.85	40.85	40.85
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Angles **Horizontal Angles**

	50	55	60	65	70	75	80	85	90	95
0	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30
5	1844.70	1803.85	1763.00	1715.70	1661.95	1608.20	1552.30	1500.70	1451.25	1401.80
10	2089.80	2038.20	1980.15	1902.75	1814.60	1720.00	1616.80	1509.30	1408.25	1315.80
15	2272.55	2203.75	2126.35	2036.05	1930.70	1801.70	1651.20	1492.10	1341.60	1214.75
20	2461.75	2356.40	2251.05	2137.10	2003.80	1851.15	1657.65	1449.10	1253.45	1096.50
25	2670.30	2552.05	2399.40	2244.60	2076.90	1881.25	1642.60	1382.45	1150.25	978.25
30	2571.40	2620.85	2534.85	2367.15	2150.00	1902.75	1601.75	1290.00	1034.15	862.15
35	2180.10	2356.40	2481.10	2423.05	2229.55	1924.25	1545.85	1186.80	918.05	754.65
40	1756.55	1952.20	2180.10	2315.55	2233.85	1937.15	1474.90	1072.85	808.40	660.05
45	1414.70	1541.55	1763.00	2027.45	2100.55	1892.00	1393.20	961.05	707.35	576.20
50	1118.00	1201.85	1352.35	1608.20	1842.55	1728.60	1279.25	855.70	617.05	500.95
55	851.40	909.45	1008.35	1193.25	1459.85	1474.90	1105.10	750.35	533.20	425.70
60	642.85	681.55	748.20	872.90	1090.05	1171.75	900.85	638.55	453.65	341.85
65	468.70	488.05	526.75	604.15	748.20	836.35	666.50	496.65	337.55	285.95
70	322.50	331.10	350.45	393.45	477.30	535.35	440.75	322.50	266.60	210.70
75	202.10	206.40	215.00	236.50	279.50	307.45	260.15	208.55	169.85	139.75
80	107.50	109.65	111.80	122.55	139.75	148.35	129.00	107.50	90.30	77.40
85	40.85	40.85	40.85	43.00	47.30	49.45	45.15	38.70	34.40	32.25
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Angles **Horizontal Angles**

	100	105	110	115	120	125	130	135	140	145
0	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30
5	1354.50	1309.35	1264.20	1225.50	1191.10	1161.00	1133.05	1105.10	1081.45	1057.80
10	1229.80	1154.55	1090.05	1027.70	971.80	924.50	885.80	851.40	823.45	799.80
15	1100.80	1012.65	928.80	864.30	808.40	761.10	724.55	694.45	668.65	651.45
20	973.95	870.75	791.20	728.85	681.55	645.00	619.20	599.85	580.50	565.45
25	851.40	752.50	683.70	634.25	597.70	565.45	543.95	524.60	507.40	500.95
30	739.60	657.90	604.15	561.15	528.90	503.10	479.45	466.55	457.95	451.50
35	649.30	582.65	535.35	494.50	468.70	445.05	432.15	423.55	412.80	408.50

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BIO-STD-FLSH-LED4-SO-AWL-D1W.IES

CANDELA TABULATION - (Cont.)

40	571.90	516.00	473.00	440.75	417.10	393.45	384.85	376.25	371.95	371.95
45	503.10	453.65	417.10	382.70	367.65	350.45	339.70	335.40	337.55	339.70
50	436.45	387.00	365.50	339.70	320.35	305.30	296.70	296.70	298.85	305.30
55	361.20	337.55	311.75	290.25	273.05	260.15	255.85	255.85	262.30	268.75
60	311.75	283.80	262.30	245.10	230.05	219.30	217.15	221.45	225.75	225.75
65	247.25	227.90	210.70	195.65	182.75	176.30	176.30	178.45	180.60	182.75
70	182.75	167.70	156.95	146.20	137.60	133.30	133.30	133.30	137.60	141.90
75	122.55	113.95	105.35	98.90	92.45	90.30	90.30	92.45	94.60	98.90
80	68.80	64.50	60.20	55.90	53.75	51.60	51.60	53.75	55.90	58.05
85	27.95	27.95	25.80	25.80	23.65	23.65	23.65	23.65	23.65	23.65
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Angles	Horizontal Angles						
	150	155	160	165	170	175	180
0	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30	1466.30
5	1038.45	1021.25	1008.35	997.60	991.15	986.85	984.70
10	782.60	765.40	752.50	741.75	735.30	731.00	731.00
15	636.40	625.65	614.90	608.45	602.00	599.85	599.85
20	552.55	541.80	533.20	526.75	522.45	522.45	522.45
25	494.50	485.90	481.60	479.45	479.45	479.45	479.45
30	449.35	449.35	442.90	440.75	440.75	440.75	440.75
35	408.50	408.50	408.50	408.50	408.50	410.65	410.65
40	374.10	378.40	380.55	380.55	382.70	384.85	387.00
45	344.00	348.30	352.60	356.90	359.05	361.20	363.35
50	311.75	316.05	316.05	316.05	313.90	313.90	316.05
55	268.75	268.75	268.75	270.90	273.05	270.90	275.20
60	227.90	230.05	232.20	234.35	234.35	234.35	234.35
65	187.05	189.20	191.35	189.20	187.05	187.05	187.05
70	144.05	146.20	141.90	139.75	135.45	133.30	131.15
75	101.05	98.90	96.75	90.30	86.00	81.70	81.70
80	58.05	55.90	53.75	49.45	45.15	43.00	43.00
85	23.65	23.65	21.50	19.35	19.35	19.35	17.20
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : BIO-STD-FLSH-LED4-SO-AWL-D1W.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	570.17	N.A.	15.20
0-30	1229.63	N.A.	32.70
0-40	1963.26	N.A.	52.20
0-60	3190.71	N.A.	84.80
0-80	3721.96	N.A.	98.90
0-90	3763.25	N.A.	100.00
10-90	3621.76	N.A.	96.20
20-40	1393.08	N.A.	37.00
20-50	2080.65	N.A.	55.30
40-70	1584.9	N.A.	42.10
60-80	531.25	N.A.	14.10
70-80	173.80	N.A.	4.60
80-90	41.29	N.A.	1.10
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	3763.25	N.A.	100.00

Total Luminaire Efficiency = N.A.%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	141.48
10-20	428.69
20-30	659.46
30-40	733.62
40-50	687.56
50-60	539.89
60-70	357.45
70-80	173.80
80-90	41.29
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : BIO-STD-FLSH-LED4-SO-AWL-D1W.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	110	106	102	98	107	103	100	97	99	96	94	95	93	91	92	90	88	86
2	101	93	87	82	98	91	86	81	88	83	79	85	81	77	82	78	75	73
3	92	83	75	69	90	81	74	68	78	72	67	75	70	66	73	69	65	63
4	85	74	66	59	83	73	65	59	70	63	58	68	62	57	66	61	57	54
5	79	66	58	52	77	65	57	51	63	56	51	61	55	50	59	54	50	48
6	73	60	52	45	71	59	51	45	57	50	45	56	49	45	54	49	44	42
7	68	55	46	40	66	54	46	40	52	45	40	51	45	40	50	44	39	38
8	63	50	42	36	62	49	42	36	48	41	36	47	40	36	46	40	36	34
9	59	46	38	33	58	46	38	33	44	37	33	43	37	32	42	37	32	31
10	55	43	35	30	54	42	35	30	41	34	30	40	34	30	39	34	29	28

POLAR GRAPH



Maximum Candela = 2825.1 Located At Horizontal Angle = 25, Vertical Angle = 20
1 - Vertical Plane Through Horizontal Angles (25 - 205) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (20) (Through Max. Cd.)