

FEATURES:

- ✓ Architectural sound absorbing luminaire combining Eco Felt Polyester with 100% Merino Wool Felt.
- ✓ Made from recyclable material available in two standard sizes.
- ✓ Polyester is Class1 Fire rated with 0.7 Noise Reduction Coefficient/1" Acoustic.
- ✓ Light source: COB LED.
- ✓ High efficiency integral reflector combined with opal lens insert provides excellent lighting distribution with 40° Beam.
- ✓ Circular internal louver is available in a wide range of finishes.
- ✓ Aluminum body of the luminaire comes with built-in-driver.
- ✓ LED Spot is rated for 60,000hrs. L70 with + 90CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:

Subsonic TUBE+

TYPE	HEIGHT	SOURCE	VOLTAGE	DRIVER	MOUNTING	LOUVER	TUBE FINISH	ACOUSTIC FINISHES	CCT
								/	

Enter the Product Code into the boxes above.

TYPE

- ☐ SS - Standard

HEIGHT

- ☐ 12 Inch
☐ 16 Inch

SOURCE

- ☐ 15W LED
☐ 20W LED
☐ 25W LED

VOLTAGE

- ☐ 120V
☐ 277V

DRIVER

- ☐ ST - Standard
☐ DL - 0-10V Dimming
☐ DT - TRIAC
☐ *

*Please specify Dimming method.

MOUNTING

- ☐ S4-Suspension 4Feet
☐ S6-Suspension 6Feet
☐ S Feet*

*Please specify required Length.

LOUVER

- ☐ WH - White
☐ BK - Black
☐ SL - Silver

TUBE FINISH

- ☐ WH - White
☐ BK - Black
☐ GR - Grey*

*Supply with White Cord & Canopy

CCT

- ☐ 30K - 3000Kelvin
☐ 35K - 3500Kelvin
☐ 40K - 4000Kelvin

*Other options are available.

WOOL FELT - TOP LAYER

<input type="checkbox"/> 111	<input type="checkbox"/> 121	<input type="checkbox"/> 131	<input type="checkbox"/> 133	<input type="checkbox"/> 145	<input type="checkbox"/> 151	<input type="checkbox"/> 164	<input type="checkbox"/> 181	<input type="checkbox"/> 182	<input type="checkbox"/> 183
------------------------------	------------------------------	------------------------------	------------------------------	------------------------------	------------------------------	------------------------------	------------------------------	------------------------------	------------------------------

POLYESTER - BASE LAYER

<input type="checkbox"/> 01	<input type="checkbox"/> 02	<input type="checkbox"/> 03	<input type="checkbox"/> 04	<input type="checkbox"/> 07	<input type="checkbox"/> 09	<input type="checkbox"/> 18	<input type="checkbox"/> 24	<input type="checkbox"/> 28	<input type="checkbox"/> 33
-----------------------------	-----------------------------	-----------------------------	-----------------------------	-----------------------------	-----------------------------	-----------------------------	-----------------------------	-----------------------------	-----------------------------

* Please specify Top Layer & Base Layer, For example (145/04)

LUMEN OUTPUT:

Watts	30K	35K	40K
15W	1400 lm	1430 lm	1460 lm
20W	1910 lm	1950 lm	1990 lm
25W	2350 lm	2400 lm	2450 lm


Project:

Type:


SIZE:

H - Height	Diameter
12 Inch = 11.75 Inch	16.00 Inch
16 Inch = 15.75 Inch	20.00 Inch


VIEW:



TOP



BOTTOM



COLOR EXAMPLES:



(145/04)



(131/04)



(151/04)



(181/04)



(164/24)



(164/28)



(121/02)



(121/09)