

Light efficiency:

75 Lumen/Watt

Light quality:

CRI: 79.7

Color temperature:


2948 K

Output: 3870 lm

Peak: 5413 cd

Power: 51.5 W

PF: 1.0




Product name:

621-6INV-XTM19-50LM-30K-83-
SA60-120-DIM10-NC

Date and time:

1/26/2018 2:36:06 PM




Beam angle

56.6°




CIE 1931
x: 0.444
y: 0.412



Spectra




Power




Color details



TM30: 78.2



CRI: 79.7 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
77.3	85.3	93.4	79.7	76.7	80.8	84.2	60.1	5.5	66.9	78.3	63.9	78.3	96.0	70.0


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
76.1	76.1	68.2	73.9	81.2	83.6	71.4	85.1	80.6	79.4	77.1	79.7	86.4	82.0	75.6	79.2

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
72.1	96.5	81.5	78.5	78.3	75.9	79.0	85.1	95.8	85.6	83.6	81.9	81.2	69.0	70.1

CQS: 79.3



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2948 K	79.7	5.5	78.2	98.4	79.3	0.444	0.412	0.252	0.351	0.0023

TM30 details







Rf 78.2

Fidelity index Rf


Rg 98.4

Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	76	-11%	-4%
2	76	-9%	8%
3	68	-3%	15%
4	74	8%	14%
5	81	11%	8%
6	84	9%	-4%
7	71	5%	-16%
8	85	-2%	-8%
9	81	-8%	-6%
10	79	-10%	2%
11	77	-8%	11%
12	80	3%	8%
13	86	8%	-1%
14	82	7%	-10%
15	76	2%	-13%
16	79	-8%	-13%



Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
5413lx	1353lx	601lx	338lx	217lx	150lx	110lx	85lx	67lx	54lx	45lx	38lx	32lx	28lx	24lx	21lx	19lx	17lx	15lx	14lx
502.9fc	125.7fc	55.9fcd	31.4fcd	20.1fcd	14fcd	10.3fcd	7.9fcd	6.2fcd	5fcd	4.2fcd	3.5fcd	3fcd	2.6fcd	2.2fcd	2fcd	1.7fcd	1.6fcd	1.4fcd	1.3fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5413	5413	5376	5178	4901	4675	4555	4434	4373	4313	4195	4045	3791	3298	2806	2019	1221	719	394	153
100%	100%	99%	96%	91%	86%	84%	82%	81%	80%	77%	75%	70%	61%	52%	37%	23%	13%	7%	3%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5413	5413	5376	5178	4901	4675	4555	4434	4373	4313	4195	4045	3791	3298	2806	2019	1221	719	394	153
100%	100%	99%	96%	91%	86%	84%	82%	81%	80%	77%	75%	70%	61%	52%	37%	23%	13%	7%	3%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5413	5413	5376	5178	4901	4675	4555	4434	4373	4313	4195	4045	3791	3298	2806	2019	1221	719	394	153
100%	100%	99%	96%	91%	86%	84%	82%	81%	80%	77%	75%	70%	61%	52%	37%	23%	13%	7%	3%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5413	5413	5376	5178	4901	4675	4555	4434	4373	4313	4195	4045	3791	3298	2806	2019	1221	719	394	153
100%	100%	99%	96%	91%	86%	84%	82%	81%	80%	77%	75%	70%	61%	52%	37%	23%	13%	7%	3%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
56.6°	70.2°	78.2°	98.6%	96.1%