

Light efficiency:

104 Lumen/Watt

Light quality:

CRI: 83.2

Color temperature:

3000 K

Output: 8971 lm

Peak: 21226 cd

Power: 86.0 W

PF: 1.0



Beam angle


32.3°

Product name:

608XK-9-CXB-90LM-30K-80-SA30-10V-MC-S


Date and time:

1/3/2018 10:11:41 AM





CIE 1931
x: 0.438
y: 0.406


Spectra




Color details



TM30: 82.9



CRI: 83.2 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
81.7	91.0	97.0	81.0	81.1	88.5	83.9	61.1	11.1	78.4	79.8	67.3	84.0	98.7	74.1

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
77.9	79.9	77.0	88.7	90.5	93.3	86.2	91.3	85.6	77.6	77.3	83.3	87.2	78.6	78.1	75.1

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	x	y	u	v	Δuv
3000 K	83.2	11.1	82.9	95.4	0.438	0.406	0.251	0.348	0.0005

TM30 details







Rf 82.9

Fidelity index Rf


Rg 95.4

Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	78	-11%	0%
2	80	-8%	6%
3	77	-3%	10%
4	89	0%	6%
5	91	-1%	4%
6	93	2%	-2%
7	86	-5%	-5%
8	91	-4%	0%
9	86	-6%	5%
10	78	-4%	12%
11	77	1%	15%
12	83	7%	4%
13	87	5%	-7%
14	79	5%	-14%
15	78	-3%	-12%
16	75	-7%	-16%



Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
21012lx	5253lx	2335lx	1313lx	840lx	584lx	429lx	328lx	259lx	210lx	174lx	146lx	124lx	107lx	93lx	82lx	73lx	65lx	58lx	53lx
1952fcd	488fcd	216.9fcd	122fcd	78.1fcd	54.2fcd	39.8fcd	30.5fcd	24.1fcd	19.5fcd	16.1fcd	13.6fcd	11.6fcd	10fcd	8.7fcd	7.6fcd	6.8fcd	6fcd	5.4fcd	4.9fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
21.0K	20.8K	20.2K	18.8K	17.5K	15.8K	14.0K	12.3K	10.7K	9.2K	8.0K	6.9K	5.9K	5.2K	4.5K	3.8K	3.2K	2.5K	1.8K	1.1K
100%	99%	96%	90%	83%	75%	67%	58%	51%	44%	38%	33%	28%	25%	21%	18%	15%	12%	9%	5%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
21.0K	20.7K	20.1K	18.7K	17.2K	15.5K	13.8K	12.1K	10.6K	9.1K	8.0K	7.0K	6.1K	5.4K	4.7K	4.0K	3.3K	2.6K	1.8K	0.9K
100%	99%	96%	89%	82%	74%	65%	58%	50%	43%	38%	33%	29%	25%	22%	19%	16%	12%	8%	5%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
21.0K	21.0K	20.0K	19.0K	17.5K	15.7K	14.0K	12.4K	10.7K	9.4K	8.2K	7.0K	6.2K	5.4K	4.7K	4.2K	3.5K	2.7K	2.0K	1.3K
100%	100%	95%	91%	83%	75%	67%	59%	51%	45%	39%	34%	30%	26%	23%	20%	17%	13%	9%	6%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
21.0K	21.0K	20.0K	19.0K	17.5K	15.8K	14.0K	12.3K	10.6K	9.2K	8.0K	6.8K	6.0K	5.2K	4.5K	3.8K	3.2K	2.5K	1.9K	1.3K
100%	100%	95%	91%	83%	75%	67%	59%	50%	44%	38%	32%	28%	25%	21%	18%	15%	12%	9%	6%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
32.3°	70.6°	81°	99.8%	99.6%