

Light efficiency:

72 Lumen/Watt

Light quality:

CRI: 80.8

Color temperature:

2963 K

Output: 1292 lm

Peak: 1369 cd


Power: 17.9 W

PF: 0.98



**112250-XTM19-20LM-30K-83-DA60-UNV-
ELV-WH-CLR**

Date and time:
12/11/2019 3:27:00 PM




Beam angle

59.9°






CIE 1931
x: 0.441
y: 0.408

Spectra




Power







TM30: 80.3



CRI: 80.8 (R1-R8)



CQS: 80.2



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
78.5	87.1	94.7	79.6	77.8	82.7	84.6	61.2	9.4	70.3	77.4	65.2	79.9	96.7	72.0

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
77.6	77.4	70.0	80.1	85.9	86.8	78.6	87.9	84.8	81.0	76.2	80.6	86.9	80.4	78.9	76.6

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
75.9	96.4	79.5	77.4	79.7	78.5	79.5	84.6	95.9	86.1	83.2	81.7	81.4	70.8	72.5

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2963 K	80.8	9.4	80.3	97.9	80.2	0.441	0.408	0.252	0.349	0.0009







Rf 80.3


Fidelity index Rf

Rg 97.9

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	78	-11%	-3%
2	77	-9%	7%
3	70	-3%	14%
4	80	5%	11%
5	86	8%	6%
6	87	7%	-3%
7	79	1%	-12%
8	88	-4%	-6%
9	85	-8%	-2%
10	81	-8%	6%
11	76	-4%	14%
12	81	5%	8%
13	87	7%	-3%
14	80	8%	-12%
15	79	1%	-12%
16	77	-7%	-15%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1365lx	341lx	152lx	85lx	55lx	38lx	28lx	21lx	17lx	14lx	11lx	9lx	8lx	7lx	6lx	5lx	5lx	4lx	4lx	3lx
126.8fcd	31.7fcd	14.1fcd	7.9fcd	5.1fcd	3.5fcd	2.6fcd	2fcd	1.6fcd	1.3fcd	1fcd	0.9fcd	0.8fcd	0.6fcd	0.6fcd	0.5fcd	0.4fcd	0.4fcd	0.4fcd	0.3fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1365	1363	1343	1323	1289	1252	1212	1167	1123	1082	1042	998	950	901	794	686	569	444	329	266
100%	100%	98%	97%	94%	92%	89%	86%	82%	79%	76%	73%	70%	66%	58%	50%	42%	33%	24%	20%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1365	1360	1343	1325	1285	1246	1199	1148	1098	1052	1006	962	919	861	768	676	556	433	331	259
100%	100%	98%	97%	94%	91%	88%	84%	80%	77%	74%	71%	67%	63%	56%	50%	41%	32%	24%	19%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1365	1361	1350	1325	1299	1259	1217	1174	1132	1089	1051	1014	959	891	815	687	558	443	333	241
100%	100%	99%	97%	95%	92%	89%	86%	83%	80%	77%	74%	70%	65%	60%	50%	41%	32%	24%	18%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1365	1357	1347	1318	1289	1253	1212	1170	1128	1086	1045	1005	954	874	793	672	544	428	333	237
100%	99%	99%	97%	94%	92%	89%	86%	83%	80%	77%	74%	70%	64%	58%	49%	40%	31%	24%	17%

Beam angle 50°	Field angle 10°	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
{B_ANG}°	88.9°	121.7°	97.4%	89.8%