

Light efficiency:

66 Lumen/Watt

Light quality:

CRI: 81.1

Color temperature:

2919 K

Output: 808 lm

Peak: 3762 cd


Power: 12.2 W

PF: 0.98




112250-XTM19-11LM-30K-83-SA20-UNV-
ELV-WH-CLR

Date and time:
12/16/2019 3:19:40 PM






CIE 1931
x: 0.452
y: 0.424

Spectra




Power






TM30: 80.0



CRI: 81.1 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
78.5	85.5	93.6	82.5	78.1	81.9	86.1	62.3	9.2	67.8	81.8	64.2	79.2	96.0	70.4


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
76.6	78.6	74.0	75.2	82.7	86.9	71.7	87.4	79.7	79.3	81.5	83.3	88.4	84.8	76.4	79.7

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
72.0	96.2	85.4	81.3	79.1	77.8	83.6	90.1	96.1	88.8	84.2	83.9	83.2	69.5	70.7

CQS: 80.9



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2919 K	81.1	9.2	80.0	97.1	80.9	0.452	0.424	0.252	0.354	0.0058







Rf 80.0


Fidelity index Rf

Rg 97.1

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	77	-10%	-4%
2	79	-9%	6%
3	74	-4%	12%
4	75	8%	13%
5	83	10%	7%
6	87	7%	-3%
7	72	5%	-16%
8	87	-2%	-7%
9	80	-7%	-8%
10	79	-10%	-3%
11	82	-10%	5%
12	83	0%	5%
13	88	6%	-3%
14	85	3%	-9%
15	76	2%	-13%
16	80	-10%	-8%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
3762lx	941lx	418lx	235lx	150lx	105lx	77lx	59lx	46lx	38lx	31lx	26lx	22lx	19lx	17lx	15lx	13lx	12lx	10lx	9lx
349.5fcd	87.4fcd	38.8fcd	21.8fcd	14fcd	9.7fcd	7.1fcd	5.5fcd	4.3fcd	3.5fcd	2.9fcd	2.4fcd	2.1fcd	1.8fcd	1.6fcd	1.4fcd	1.2fcd	1.1fcd	1fcd	0.9fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3762	3603	3229	2698	2169	1775	1422	1140	930	774	646	539	456	385	318	248	181	120	69	33
100%	96%	86%	72%	58%	47%	38%	30%	25%	21%	17%	14%	12%	10%	8%	7%	5%	3%	2%	1%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3762	3603	3229	2698	2169	1775	1422	1140	930	774	646	539	456	385	318	248	181	120	69	33
100%	96%	86%	72%	58%	47%	38%	30%	25%	21%	17%	14%	12%	10%	8%	7%	5%	3%	2%	1%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3762	3603	3229	2698	2169	1775	1422	1140	930	774	646	539	456	385	318	248	181	120	69	33
100%	96%	86%	72%	58%	47%	38%	30%	25%	21%	17%	14%	12%	10%	8%	7%	5%	3%	2%	1%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
3762	3603	3229	2698	2169	1775	1422	1140	930	774	646	539	456	385	318	248	181	120	69	33
100%	96%	86%	72%	58%	47%	38%	30%	25%	21%	17%	14%	12%	10%	8%	7%	5%	3%	2%	1%

Beam angle 50°	Field angle 10°	Cutoff angle 2,5°	Intensity ratio in 120° cone	Intensity ratio in 90° cone
{B_ANG}°	52.5°	69.7°	98.9%	97.8%