

Light efficiency:

71 Lumen/Watt

Light quality:

CRI: 82.9

Color temperature:

2926 K

Output: 1076 lm

Peak: 1343 cd


Power: 15.3 W

PF: 0.98



112250-XTM19-16LM-30K-83-SSA60-  
UNV-ELV-WH-CLR

Date and time:  
12/13/2019 11:26:50 AM




Beam angle

57.2°






CIE 1931  
x: 0.444  
y: 0.409

Spectra




Power






TM30: 81.9



CRI: 82.9 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
80.9	88.5	95.7	82.5	80.7	85.6	85.3	63.5	15.4	74.1	81.9	71.4	82.2	97.4	74.0


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
79.2	79.4	72.8	80.6	85.8	86.9	78.1	89.0	85.7	84.1	80.6	82.7	87.4	81.7	79.4	79.0

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
76.0	96.4	83.0	81.5	82.2	80.4	82.0	86.4	96.1	87.7	85.5	83.8	83.2	72.6	73.7

CQS: 82.0



## Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	$\Delta uv$
2926 K	82.9	15.4	81.9	98.8	82.0	0.444	0.409	0.253	0.349	0.0009







**Rf 81.9**


Fidelity index Rf

**Rg 98.8**

Gamut index Rg

Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	79	-10%	-3%
2	79	-8%	7%
3	73	-3%	13%
4	81	5%	11%
5	86	8%	6%
6	87	7%	-3%
7	78	2%	-12%
8	89	-2%	-6%
9	86	-7%	-4%
10	84	-8%	3%
11	81	-5%	11%
12	83	4%	6%
13	87	7%	-3%
14	82	6%	-11%
15	79	1%	-11%
16	79	-7%	-13%





**Beam intensities from 1-20m**

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1343lx	336lx	149lx	84lx	54lx	37lx	27lx	21lx	17lx	13lx	11lx	9lx	8lx	7lx	6lx	5lx	5lx	4lx	4lx	3lx
124.8fcd	31.2fcd	13.9fcd	7.8fcd	5fcd	3.5fcd	2.5fcd	1.9fcd	1.5fcd	1.2fcd	1fcd	0.9fcd	0.7fcd	0.6fcd	0.6fcd	0.5fcd	0.4fcd	0.4fcd	0.3fcd	0.3fcd

**Intensities in 0° c-plane**

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1343	1339	1328	1311	1286	1253	1213	1166	1113	1058	1007	954	892	812	710	585	454	332	228	151
100%	100%	99%	98%	96%	93%	90%	87%	83%	79%	75%	71%	66%	60%	53%	44%	34%	25%	17%	11%

**Intensities in 90° c-plane**

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1343	1339	1328	1311	1286	1253	1213	1166	1113	1058	1007	954	892	812	710	585	454	332	228	151
100%	100%	99%	98%	96%	93%	90%	87%	83%	79%	75%	71%	66%	60%	53%	44%	34%	25%	17%	11%

**Intensities in 180° c-plane**

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1343	1339	1328	1311	1286	1253	1213	1166	1113	1058	1007	954	892	812	710	585	454	332	228	151
100%	100%	99%	98%	96%	93%	90%	87%	83%	79%	75%	71%	66%	60%	53%	44%	34%	25%	17%	11%

**Intensities in 270° c-plane**

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1343	1339	1328	1311	1286	1253	1213	1166	1113	1058	1007	954	892	812	710	585	454	332	228	151
100%	100%	99%	98%	96%	93%	90%	87%	83%	79%	75%	71%	66%	60%	53%	44%	34%	25%	17%	11%

Beam angle 50°	Field angle 10°	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
{B_ANG}°	77.4°	98°	98.7%	95.7%