



IES ROAD REPORT
PHOTOMETRIC FILENAME : GCJ2-20H-MV-CW-4-XX-830 S.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TESTLAB] Scaled from GCJ2-20H-MV-CW-4-XX-700, L091603908
[ISSUEDATE] 9/29/2016
[MANUFAC] Leotek Electronics USA, LLC
[LUMCAT] GCJ2-20H-MV-CW-4-XX-830 S
[LUMINAIRE] 18.25"L. X 9.5"W. X 4.5"H. LED STREET LIGHT


CHARACTERISTICS

IES Classification	Type IV
Longitudinal Classification	Medium
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	6320
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	118
Total Luminaire Watts	53.5
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	3506.661
Maximum Candela Angle	80H 71V
Maximum Candela (<90 Degrees Vertical)	3506.661
Maximum Candela Angle (<90 Degrees Vertical)	80H 71V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	275.728 (4.4% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

LUMINAIRE CLASSIFICATION SYSTEM (LCS)


	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	609.0	N.A.	9.6
FM - Front-Medium (30-60)	1661.7	N.A.	26.3
FH - Front-High (60-80)	1664.7	N.A.	26.3
FVH - Front-Very High (80-90)	22.7	N.A.	0.4
BL - Back-Low (0-30)	528.1	N.A.	8.4
BM - Back-Medium (30-60)	1342.7	N.A.	21.2
BH - Back-High (60-80)	481.9	N.A.	7.6
BVH - Back-Very High (80-90)	9.6	N.A.	0.2
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
Total	6320.4	N.A.	100.0
BUG Rating	B2-U0-G1		

POLAR GRAPH




Maximum Candela = 3506.661 Located At Horizontal Angle = 80, Vertical Angle = 71
1 - Vertical Plane Through Horizontal Angles (80 - 260) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (71) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



Distance In Units Of Mounting Height
 Values Based On 25 Foot Mounting Height
 1/2 Maximum Candela Trace Shown As Dashed Curve
 (+) = Maximum Candela Point

LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
 Front: Low=609.0, Medium=1661.7, High=1664.7, Very High=22.7
 Back: Low=528.1, Medium=1342.7, High=481.9, Very High=9.6
 Uplight: Low=0.0, High=0.0

BUG Rating : B2-U0-G1