

Light efficiency:

84 Lumen/Watt

Light quality:

CRI: 83.5

Color temperature:

2945 K

Output: 739 lm

Peak: 2824 cd

Power: 8.8 W

PF: 0.96




Product name:

**608RA-4-XTM19-10LM-30K-83-S20-120-ELV-BK-BK-P**


Date and time:

**1/26/2019 1:18:22 PM**






CIE 1931  
x: 0.443  
y: 0.409

Spectra




Power






TM30: 81.6



CRI: 83.5 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
82.0	88.4	94.5	84.0	81.6	85.3	86.3	66.3	21.0	73.6	83.7	71.5	82.9	96.5	75.5


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
80.0	80.5	73.3	78.4	84.0	85.5	75.7	87.9	84.4	83.7	81.3	82.6	87.6	83.3	79.2	81.2

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
75.9	96.7	83.9	82.3	82.1	79.8	82.5	87.3	96.3	87.7	86.2	84.9	84.5	74.1	74.7

CQS: 82.5



## Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	$\Delta uv$
2945 K	83.5	21.0	81.6	99.7	82.5	0.443	0.409	0.252	0.350	0.0012

## TM30 Details







**Rf 81.6**

Fidelity index Rf


**Rg 99.7**

Gamut index Rg

Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	80	-9%	-4%
2	80	-8%	6%
3	73	-2%	13%
4	78	7%	11%
5	84	10%	7%
6	86	8%	-3%
7	76	4%	-13%
8	88	-1%	-7%
9	84	-6%	-5%
10	84	-8%	1%
11	81	-6%	9%
12	83	3%	6%
13	88	7%	-2%
14	83	6%	-10%
15	79	2%	-11%
16	81	-6%	-12%



## Beam Details



### Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2824lx	706lx	314lx	177lx	113lx	78lx	58lx	44lx	35lx	28lx	23lx	20lx	17lx	14lx	13lx	11lx	10lx	9lx	8lx	7lx
262.4fcd	65.6fcd	29.2fcd	16.4fcd	10.5fcd	7.3fcd	5.4fcd	4.1fcd	3.2fcd	2.6fcd	2.2fcd	1.8fcd	1.6fcd	1.3fcd	1.2fcd	1fcd	0.9fcd	0.8fcd	0.7fcd	0.7fcd

### Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2824	2672	2464	2212	1857	1503	1247	1008	816	689	563	488	414	355	309	263	214	164	120	79
100%	95%	87%	78%	66%	53%	44%	36%	29%	24%	20%	17%	15%	13%	11%	9%	8%	6%	4%	3%

### Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2824	2672	2464	2212	1857	1503	1247	1008	816	689	563	488	414	355	309	263	214	164	120	79
100%	95%	87%	78%	66%	53%	44%	36%	29%	24%	20%	17%	15%	13%	11%	9%	8%	6%	4%	3%

### Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2824	2672	2464	2212	1857	1503	1247	1008	816	689	563	488	414	355	309	263	214	164	120	79
100%	95%	87%	78%	66%	53%	44%	36%	29%	24%	20%	17%	15%	13%	11%	9%	8%	6%	4%	3%

### Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2824	2672	2464	2212	1857	1503	1247	1008	816	689	563	488	414	355	309	263	214	164	120	79
100%	95%	87%	78%	66%	53%	44%	36%	29%	24%	20%	17%	15%	13%	11%	9%	8%	6%	4%	3%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
21.2°	58.3°	76.8°	99.3%	98.0%