

Light efficiency:

79 Lumen/Watt

Light quality:

CRI: 83.5

Color temperature:

2951 K

Output: 1066 lm

Peak: 1552 cd

Power: 13.5 W

PF: 0.99




Product name:

608RA-4-XTM19-15LM-30K-83-HE40-120-ELV-BK-BK-P

Date and time:

1/26/2019 9:44:30 AM




Beam angle

42.3°






CIE 1931
x: 0.443
y: 0.410

Spectra




Power







TM30: 82.5



CRI: 83.5 (R1-R8)



CQS: 82.8



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
81.7	88.4	94.9	83.7	81.3	85.3	86.5	65.9	19.9	73.7	83.0	71.1	82.7	96.8	75.1

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
80.1	80.7	74.2	80.8	85.9	87.2	78.4	89.3	85.7	84.4	81.3	83.2	88.0	82.9	80.1	80.3

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
76.9	96.5	83.8	82.2	82.6	80.8	83.0	87.5	96.3	88.1	86.4	85.0	84.4	73.9	74.9

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2951 K	83.5	19.9	82.5	99.0	82.8	0.443	0.410	0.252	0.350	0.0017

TM30 Details







Rf 82.5

Fidelity index Rf


Rg 99.0

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	80	-9%	-3%
2	81	-8%	6%
3	74	-3%	12%
4	81	5%	10%
5	86	8%	6%
6	87	7%	-3%
7	78	3%	-12%
8	89	-2%	-6%
9	86	-6%	-4%
10	84	-8%	2%
11	81	-5%	10%
12	83	4%	6%
13	88	6%	-3%
14	83	6%	-10%
15	80	1%	-11%
16	80	-6%	-13%



Beam Details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1552lx	388lx	172lx	97lx	62lx	43lx	32lx	24lx	19lx	16lx	13lx	11lx	9lx	8lx	7lx	6lx	5lx	5lx	4lx	4lx
144.2fcd	36fcd	16fcd	9fcd	5.8fcd	4fcd	2.9fcd	2.3fcd	1.8fcd	1.4fcd	1.2fcd	1fcd	0.9fcd	0.7fcd	0.6fcd	0.6fcd	0.5fcd	0.4fcd	0.4fcd	0.4fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1552	1544	1506	1468	1398	1318	1233	1132	1031	932	832	738	653	568	501	435	377	328	279	242
100%	100%	97%	95%	90%	85%	79%	73%	66%	60%	54%	48%	42%	37%	32%	28%	24%	21%	18%	16%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1552	1544	1506	1468	1398	1318	1233	1132	1031	932	832	738	653	568	501	435	377	328	279	242
100%	100%	97%	95%	90%	85%	79%	73%	66%	60%	54%	48%	42%	37%	32%	28%	24%	21%	18%	16%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1552	1544	1506	1468	1398	1318	1233	1132	1031	932	832	738	653	568	501	435	377	328	279	242
100%	100%	97%	95%	90%	85%	79%	73%	66%	60%	54%	48%	42%	37%	32%	28%	24%	21%	18%	16%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1552	1544	1506	1468	1398	1318	1233	1132	1031	932	832	738	653	568	501	435	377	328	279	242
100%	100%	97%	95%	90%	85%	79%	73%	66%	60%	54%	48%	42%	37%	32%	28%	24%	21%	18%	16%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
42.3°	87.1°	111.2°	98.7%	90.8%