

Light efficiency:

69 Lumen/Watt

Light quality:

CRI: 82.6

Color temperature:

2936 K

Output: 1306 lm

Peak: 1746 cd

Power: 18.9 W

PF: 0.99




Product name:

A15-3-XTM19-20LM-30K-83-S50-NL-120-DIM10-WH-WH-P

Date and time:

1/23/2019 3:15:01 PM




Beam angle

51.4°






CIE 1931
x: 0.444
y: 0.409

Spectra




Power






TM30: 82.3



CRI: 82.6 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
80.5	88.4	95.7	81.8	80.1	85.0	85.6	63.8	15.9	73.6	80.4	70.0	81.8	97.3	74.0


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
79.3	79.5	73.1	82.1	87.2	88.1	80.0	89.5	86.3	83.7	79.8	82.8	87.8	81.7	80.2	78.6

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
77.1	96.3	82.4	80.5	81.9	80.6	81.9	86.3	96.1	87.7	85.3	83.6	83.0	72.8	74.2

CQS: 82.0



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2936 K	82.6	15.9	82.3	98.2	82.0	0.444	0.409	0.253	0.350	0.0011

TM30 Details







Rf 82.3

Fidelity index Rf


Rg 98.2

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	79	-10%	-2%
2	79	-8%	7%
3	73	-3%	13%
4	82	4%	10%
5	87	7%	6%
6	88	6%	-3%
7	80	1%	-11%
8	89	-3%	-5%
9	86	-7%	-2%
10	84	-7%	5%
11	80	-4%	12%
12	83	5%	6%
13	88	6%	-3%
14	82	6%	-11%
15	80	1%	-11%
16	79	-7%	-14%



Beam Details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1746lx	437lx	194lx	109lx	70lx	49lx	36lx	27lx	22lx	17lx	14lx	12lx	10lx	9lx	8lx	7lx	6lx	5lx	5lx	4lx
162.3fcd	40.6fcd	18fcd	10.1fcd	6.5fcd	4.5fcd	3.3fcd	2.5fcd	2fcd	1.6fcd	1.3fcd	1.1fcd	1fcd	0.8fcd	0.7fcd	0.6fcd	0.6fcd	0.5fcd	0.4fcd	0.4fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1746	1744	1721	1699	1658	1606	1550	1468	1387	1290	1186	1081	968	856	748	643	540	445	350	273
100%	100%	99%	97%	95%	92%	89%	84%	79%	74%	68%	62%	55%	49%	43%	37%	31%	25%	20%	16%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1746	1744	1721	1699	1658	1606	1550	1468	1387	1290	1186	1081	968	856	748	643	540	445	350	273
100%	100%	99%	97%	95%	92%	89%	84%	79%	74%	68%	62%	55%	49%	43%	37%	31%	25%	20%	16%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1746	1744	1721	1699	1658	1606	1550	1468	1387	1290	1186	1081	968	856	748	643	540	445	350	273
100%	100%	99%	97%	95%	92%	89%	84%	79%	74%	68%	62%	55%	49%	43%	37%	31%	25%	20%	16%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1746	1744	1721	1699	1658	1606	1550	1468	1387	1290	1186	1081	968	856	748	643	540	445	350	273
100%	100%	99%	97%	95%	92%	89%	84%	79%	74%	68%	62%	55%	49%	43%	37%	31%	25%	20%	16%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
51.4°	81.7°	96.7°	99.3%	97.2%