

Light efficiency:

83 Lumen/Watt

Light quality:

CRI: 84.6

Color temperature:

3036 K

Output: 1306 lm

Peak: 1798 cd

Power: 15.7 W

PF: 1.0




Product name:

A25-4-RH-SW-20LM-30K-80-WHD50-SMT-CAS-WH

Date and time:

2/20/2019 1:59:17 PM




Beam angle

51.2°






CIE 1931
x: 0.436
y: 0.406

Spectra




Power






TM30: 85.3



CRI: 84.6 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
83.4	92.6	96.3	83.6	83.9	91.8	83.8	61.6	12.8	83.6	84.1	75.6	85.7	98.6	74.9


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
79.1	81.7	80.5	91.6	92.9	94.4	87.9	93.6	89.0	82.6	83.2	85.5	86.5	78.5	78.2	76.2

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
78.8	94.6	86.3	83.6	85.7	86.3	86.2	88.7	95.1	92.2	89.2	86.4	84.5	72.9	75.0

CQS: 84.3









Color parameters


Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3036 K	84.6	12.8	85.3	95.5	84.3	0.436	0.406	0.249	0.348	0.0010

Fidelity index R_f

Gammut index Rg

		Graphic shifts (%)	
Hue Bin	R_f	Chroma	Hue
1	79	-10%	0%
2	82	-7%	6%
3	80	-3%	9%
4	92	0%	4%
5	93	-1%	3%
6	94	1%	-2%
7	88	-5%	-4%
8	94	-3%	0%
9	89	-5%	4%
10	83	-3%	8%
11	83	1%	11%
12	86	6%	1%
13	87	4%	-8%
14	79	4%	-15%
15	78	-4%	-12%
16	76	-8%	-15%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1798lx	449lx	200lx	112lx	72lx	50lx	37lx	28lx	22lx	18lx	15lx	12lx	11lx	9lx	8lx	7lx	6lx	6lx	5lx	4lx
167fcd	41.8fcd	18.6fcd	10.4fcd	6.7fcd	4.6fcd	3.4fcd	2.6fcd	2.1fcd	1.7fcd	1.4fcd	1.2fcd	1fcd	0.9fcd	0.7fcd	0.7fcd	0.6fcd	0.5fcd	0.5fcd	0.4fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1798	1786	1766	1743	1689	1635	1571	1501	1429	1348	1266	1147	1009	864	693	521	409	320	240	189
100%	99%	98%	97%	94%	91%	87%	83%	79%	75%	70%	64%	56%	48%	39%	29%	23%	18%	13%	11%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1798	1786	1766	1743	1689	1635	1571	1501	1429	1348	1266	1147	1009	864	693	521	409	320	240	189
100%	99%	98%	97%	94%	91%	87%	83%	79%	75%	70%	64%	56%	48%	39%	29%	23%	18%	13%	11%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1798	1786	1766	1743	1689	1635	1571	1501	1429	1348	1266	1147	1009	864	693	521	409	320	240	189
100%	99%	98%	97%	94%	91%	87%	83%	79%	75%	70%	64%	56%	48%	39%	29%	23%	18%	13%	11%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1798	1786	1766	1743	1689	1635	1571	1501	1429	1348	1266	1147	1009	864	693	521	409	320	240	189
100%	99%	98%	97%	94%	91%	87%	83%	79%	75%	70%	64%	56%	48%	39%	29%	23%	18%	13%	11%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
51.2°	76.8°	113°	97.8%	92.3%