

Light efficiency:

83 Lumen/Watt

Light quality:

CRI: 84.7

Color temperature:

3048 K

Output: 1889 lm

Peak: 5893 cd

Power: 22.7 W

PF: 1.0




Product name:

A25-4-RH-SW-27LM-30K-80-BKS30-SMT-CAS-WH


Date and time:

2/20/2019 12:58:23 PM






CIE 1931
x: 0.434
y: 0.404

Spectra




Power






TM30: 85.2



CRI: 84.7 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
83.6	92.8	96.2	83.7	84.1	92.0	83.6	61.5	12.7	83.9	84.3	76.2	86.0	98.6	75.2


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
79.1	81.5	80.0	91.2	92.8	94.1	87.9	93.9	89.3	82.7	83.1	85.4	86.5	78.6	78.2	76.3

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
78.8	94.7	85.9	83.3	85.6	86.3	86.1	88.2	95.2	91.8	88.8	86.0	84.3	72.9	74.8

CQS: 84.1



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3048 K	84.7	12.7	85.2	95.8	84.1	0.434	0.404	0.249	0.347	0.0003







Rf 85.2

Fidelity index Rf


Rg 95.8

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	79	-11%	0%
2	82	-7%	6%
3	80	-3%	9%
4	91	0%	5%
5	93	-1%	3%
6	94	1%	-2%
7	88	-4%	-5%
8	94	-3%	0%
9	89	-5%	4%
10	83	-3%	8%
11	83	1%	11%
12	85	6%	1%
13	86	4%	-8%
14	79	4%	-15%
15	78	-3%	-12%
16	76	-8%	-15%



Beam Details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
5893lx	1473lx	655lx	368lx	236lx	164lx	120lx	92lx	73lx	59lx	49lx	41lx	35lx	30lx	26lx	23lx	20lx	18lx	16lx	15lx
547.4fcd	136.9fcd	60.8fcd	34.2fcd	21.9fcd	15.2fcd	11.2fcd	8.6fcd	6.8fcd	5.5fcd	4.5fcd	3.8fcd	3.2fcd	2.8fcd	2.4fcd	2.1fcd	1.9fcd	1.7fcd	1.5fcd	1.4fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5893	5793	5591	5389	4903	4417	3904	3365	2828	2397	1966	1579	1232	888	630	371	206	118	35	23
100%	98%	95%	91%	83%	75%	66%	57%	48%	41%	33%	27%	21%	15%	11%	6%	3%	2%	1%	0%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5893	5793	5591	5389	4903	4417	3904	3365	2828	2397	1966	1579	1232	888	630	371	206	118	35	23
100%	98%	95%	91%	83%	75%	66%	57%	48%	41%	33%	27%	21%	15%	11%	6%	3%	2%	1%	0%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5893	5793	5591	5389	4903	4417	3904	3365	2828	2397	1966	1579	1232	888	630	371	206	118	35	23
100%	98%	95%	91%	83%	75%	66%	57%	48%	41%	33%	27%	21%	15%	11%	6%	3%	2%	1%	0%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
5893	5793	5591	5389	4903	4417	3904	3365	2828	2397	1966	1579	1232	888	630	371	206	118	35	23
100%	98%	95%	91%	83%	75%	66%	57%	48%	41%	33%	27%	21%	15%	11%	6%	3%	2%	1%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
31.1°	56.6°	66.7°	99.7%	99.6%