


Product Photometry and ies files are also available online at www.finelite.com.
For layouts or additional photometry, contact your local representative or the factory.

S15: 1 T8 LSI REPORT 18056




EFFICIENCY = 73.4%

80% Uplight
20% Downlight



CANDELA DISTRIBUTION		FLUX
0.0	22.5	45.0
0	168	168
5	166	167
15	159	160
25	144	146
35	122	126
45	95	98
55	63	67
65	31	34
75	10	14
85	1	4
90	0	18
95	19	131
105	67	212
115	121	194
125	170	207
135	212	232
145	244	257
155	270	274
165	286	287
175	294	293
180	293	293




ZONAL LUMEN SUMMARY			
ZONE	LUMENS	%LAMP	%FIXT
0-30	129	4.33	5.90
0-40	210	7.02	9.56
0-60	353	11.80	16.07
0-90	432	14.80	19.63
40-90	221	7.39	10.07
60-90	78	2.61	3.56
90-180	1769	58.99	80.37
0-180	2201	73.39	100.00

S15: 2 T8 LSI REPORT 18057



EFFICIENCY = 71.2%

78% Uplight
22% Downlight



CANDELA DISTRIBUTION		FLUX
0.0	22.5	45.0
0	382	382
5	378	379
15	361	363
25	326	330
35	277	284
45	213	220
55	139	149
65	68	76
75	21	30
85	2	9
90	0	33
95	28	186
105	123	365
115	232	395
125	336	442
135	423	495
145	495	538
155	548	567
165	584	589
175	603	602
180	603	603




ZONAL LUMEN SUMMARY			
ZONE	LUMENS	%LAMP	%FIXT
0-30	293	4.89	6.86
0-40	474	7.90	11.10
0-60	794	13.25	18.60
0-90	961	16.02	22.49
40-90	487	8.12	11.39
60-90	166	2.77	3.89
90-180	3312	55.22	77.51
0-180	4274	71.24	100.00

S15: 1 T5HO LSI REPORT 18033




EFFICIENCY = 81.9%

75% Uplight
25% Downlight



CANDELA DISTRIBUTION		FLUX
0.0	22.5	45
0	371	371
5	369	370
15	348	349
25	309	313
35	258	265
45	197	202
55	129	136
65	69	75
75	29	33
85	3	11
90	1	41
95	24	209
105	100	338
115	181	333
125	257	329
135	320	356
145	369	389
155	405	412
165	428	429
175	442	438
180	439	439




ZONAL LUMEN SUMMARY			
ZONE	LUMENS	%LAMP	%FIXT
0-30	280	6.24	7.61
0-40	449	9.99	12.19
0-60	741	16.48	20.12
0-90	919	20.44	24.96
40-90	470	10.46	12.77
60-90	178	3.96	4.84
90-180	2766	61.47	75.04
0-180	3686	81.92	100.00

S15: 2 T5HO LSI REPORT 18100



EFFICIENCY = 77.6%

76% Uplight
24% Downlight



CANDELA DISTRIBUTION		FLUX
0.0	22.5	45
0	692	692
5	689	689
15	652	652
25	579	584
35	482	491
45	366	376
55	239	251
65	127	139
75	53	61
85	5	19
90	0	0
95	45	361
105	187	627
115	341	620
125	481	637
135	600	691
145	696	746
155	766	786
165	813	817
175	835	833
180	832	832



ZONAL LUMEN SUMMARY			
ZONE	LUMENS	%LAMP	%FIXT
0-30	521	5.79	7.46
0-40	833	9.26	11.93
0-60	1375	15.28	19.69
0-90	1695	18.84	24.28
40-90	862	9.58	12.34
60-90	320	3.56	4.58
90-180	5289	58.77	75.72
0-180	6984	77.61	100.00

© 2009 FINELITE, INC. ALL RIGHTS RESERVED. Form CP13079.04/09 A