

Light efficiency:

77 Lumen/Watt

Light quality:

CRI: 79.7

Color temperature:

2932 K

Output: 3930 lm

Peak: 6119 cd

Power: 51.0 W

PF: 1.0



Beam angle


51.7°

Product name:

608RA-6-XTM19-50LM-30K-83-  
SA60-UNV-DIM10-MC-S-CRO


Date and time:

12/5/2017 9:04:18 AM





CIE 1931  
x: 0.446  
y: 0.413


Spectra




## Color details



TM30: 77.9



CRI: 79.7 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
77.3	85.2	93.1	79.8	76.6	80.6	84.3	60.3	5.8	66.5	78.4	63.5	78.3	95.8	70.0

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
75.9	76.2	68.2	73.0	80.6	83.2	70.3	84.7	79.9	79.0	77.3	79.6	86.3	82.3	75.2	79.2

## Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	x	y	u	v	Δuv
2932 K	79.7	5.8	77.9	98.5	0.446	0.413	0.252	0.351	0.0025

## TM30 details







**Rf 77.9**

Fidelity index Rf


**Rg 98.5**

Gammut index Rg

Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	76	-11%	-4%
2	76	-9%	8%
3	68	-3%	15%
4	73	8%	14%
5	81	12%	8%
6	83	9%	-4%
7	70	5%	-16%
8	85	-2%	-9%
9	80	-8%	-7%
10	79	-11%	1%
11	77	-8%	11%
12	80	3%	8%
13	86	8%	-1%
14	82	7%	-10%
15	75	3%	-13%
16	79	-8%	-12%



## Beam details



### Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
6119lx	1530lx	680lx	382lx	245lx	170lx	125lx	96lx	76lx	61lx	51lx	42lx	36lx	31lx	27lx	24lx	21lx	19lx	17lx	15lx
568.5fcd	142.1fcd	63.2fcd	35.5fcd	22.7fcd	15.8fcd	11.6fcd	8.9fcd	7fcd	5.7fcd	4.7fcd	3.9fcd	3.4fcd	2.9fcd	2.5fcd	2.2fcd	2fcd	1.8fcd	1.6fcd	1.4fcd

### Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
6119	6119	6000	5842	5675	5483	5291	5097	4903	4665	4316	3966	3510	3024	2494	1862	1229	773	360	71
100%	100%	98%	95%	93%	90%	86%	83%	80%	76%	71%	65%	57%	49%	41%	30%	20%	13%	6%	1%

### Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
6119	6119	6000	5842	5675	5483	5291	5097	4903	4665	4316	3966	3510	3024	2494	1862	1229	773	360	71
100%	100%	98%	95%	93%	90%	86%	83%	80%	76%	71%	65%	57%	49%	41%	30%	20%	13%	6%	1%

### Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
6119	6119	6000	5842	5675	5483	5291	5097	4903	4665	4316	3966	3510	3024	2494	1862	1229	773	360	71
100%	100%	98%	95%	93%	90%	86%	83%	80%	76%	71%	65%	57%	49%	41%	30%	20%	13%	6%	1%

### Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
6119	6119	6000	5842	5675	5483	5291	5097	4903	4665	4316	3966	3510	3024	2494	1862	1229	773	360	71
100%	100%	98%	95%	93%	90%	86%	83%	80%	76%	71%	65%	57%	49%	41%	30%	20%	13%	6%	1%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
51.7°	69.6°	74°	97.8%	96.7%