

Light efficiency:

**79 Lumen/Watt**

Light quality:

**CRI: 84.3**

Color temperature:

**3004 K**

**Output: 678 lm**

**Peak: 910 cd**

**Power: 8.6 W**

**PF: 0.94**




Product name:

**624-RD-SW-10LM-30K-80-D50-120-DIM10-NC-WH-WH**

Date and time:

**1/30/2019 9:16:03 AM**




Beam angle

**50.6°**






CIE 1931  
x: 0.440  
y: 0.411

Spectra




Power






**TM30: 85.0**



**CRI: 84.3 (R1-R8)**



**CRI R values, only R1-R8 are used to calculate final CRI value**

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
82.9	92.3	96.5	83.1	83.2	91.6	83.9	60.9	11.1	82.9	83.6	73.7	85.2	98.6	74.0


**TM30 C values, 16 binned values out of total of 99 C values**

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
78.5	81.8	81.7	92.2	92.6	94.6	87.5	92.5	87.4	82.7	83.1	85.7	86.1	78.1	77.8	75.6

**CQS Q values**

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
78.5	94.0	87.1	83.8	85.4	85.8	86.0	89.6	95.0	93.0	90.0	87.1	84.9	72.4	74.8

**CQS: 84.3**



### Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	$\Delta uv$
3004 K	84.3	11.1	85.0	94.4	84.3	0.440	0.411	0.250	0.350	0.0024

## TM30 Details







**Rf 85.0**


Fidelity index Rf

**Rg 94.4**

Gamut index Rg

Hue Bin	R <sub>f</sub>	Graphic shifts (%)	
		Chroma	Hue
1	78	-11%	0%
2	82	-7%	5%
3	82	-4%	8%
4	92	-1%	3%
5	93	-3%	2%
6	95	-1%	-1%
7	87	-6%	-3%
8	92	-3%	2%
9	87	-5%	5%
10	83	-3%	9%
11	83	1%	11%
12	86	6%	1%
13	86	3%	-9%
14	78	3%	-16%
15	78	-4%	-12%
16	76	-8%	-15%





### Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
910lx	228lx	101lx	57lx	36lx	25lx	19lx	14lx	11lx	9lx	8lx	6lx	5lx	5lx	4lx	4lx	3lx	3lx	3lx	2lx
84.6fcd	21.1fcd	9.4fcd	5.3fcd	3.4fcd	2.3fcd	1.7fcd	1.3fcd	1fcd	0.8fcd	0.7fcd	0.6fcd	0.5fcd	0.4fcd	0.4fcd	0.3fcd	0.3fcd	0.3fcd	0.2fcd	0.2fcd

### Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
910	904	898	881	850	819	779	738	699	660	620	560	499	429	351	277	222	168	136	114
100%	99%	99%	97%	93%	90%	86%	81%	77%	72%	68%	61%	55%	47%	39%	30%	24%	18%	15%	13%

### Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
910	904	898	881	850	819	779	738	699	660	620	560	499	429	351	277	222	168	136	114
100%	99%	99%	97%	93%	90%	86%	81%	77%	72%	68%	61%	55%	47%	39%	30%	24%	18%	15%	13%

### Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
910	904	898	881	850	819	779	738	699	660	620	560	499	429	351	277	222	168	136	114
100%	99%	99%	97%	93%	90%	86%	81%	77%	72%	68%	61%	55%	47%	39%	30%	24%	18%	15%	13%

### Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
910	904	898	881	850	819	779	738	699	660	620	560	499	429	351	277	222	168	136	114
100%	99%	99%	97%	93%	90%	86%	81%	77%	72%	68%	61%	55%	47%	39%	30%	24%	18%	15%	13%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
50.6°	81°	112.7°	97.7%	91.2%