

Light efficiency:

78 Lumen/Watt

Light quality:

CRI: 84.4

Color temperature:

3056 K

Output: 1758 lm

Peak: 2006 cd

Power: 22.6 W

PF: 0.97




Product name:

NU3-RD-SW-27LM-30K-80-D60-NL-120-NC-WH-WH

Date and time:

2/7/2019 4:01:17 PM




Beam angle

57°






CIE 1931
x: 0.435
y: 0.406

Spectra




Power







TM30: 85.0



CRI: 84.4 (R1-R8)



CQS: 84.1



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
83.2	92.7	96.0	83.0	83.6	91.8	83.5	61.2	12.0	83.7	83.3	75.1	85.6	98.4	74.7

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
78.7	81.5	80.6	91.8	92.7	94.4	87.6	92.8	88.1	81.4	82.9	86.0	86.4	78.3	77.9	75.8

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
78.8	94.5	86.3	83.0	85.0	85.7	85.8	88.5	95.1	92.2	89.1	86.1	84.3	72.7	74.8

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3056 K	84.4	12.0	85.0	95.2	84.1	0.435	0.406	0.248	0.348	0.0009







Rf 85.0


Fidelity index Rf

Rg 95.2

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	79	-11%	0%
2	81	-7%	6%
3	81	-3%	9%
4	92	-1%	4%
5	93	-2%	2%
6	94	0%	-2%
7	88	-5%	-4%
8	93	-3%	1%
9	88	-5%	5%
10	81	-3%	9%
11	83	1%	10%
12	86	7%	-1%
13	86	3%	-8%
14	78	4%	-16%
15	78	-4%	-12%
16	76	-8%	-15%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
2000lx	500lx	222lx	125lx	80lx	56lx	41lx	31lx	25lx	20lx	17lx	14lx	12lx	10lx	9lx	8lx	7lx	6lx	6lx	5lx
185.8fcd	46.4fcd	20.6fcd	11.6fcd	7.4fcd	5.2fcd	3.8fcd	2.9fcd	2.3fcd	1.9fcd	1.5fcd	1.3fcd	1.1fcd	0.9fcd	0.8fcd	0.7fcd	0.6fcd	0.6fcd	0.5fcd	0.5fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2000	2006	1985	1958	1922	1866	1810	1739	1664	1588	1508	1428	1309	1184	1048	892	737	597	458	353
100%	100%	99%	98%	96%	93%	90%	87%	83%	79%	75%	71%	65%	59%	52%	45%	37%	30%	23%	18%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2000	1986	1972	1956	1908	1860	1798	1727	1655	1575	1495	1398	1293	1178	1027	877	728	580	448	361
100%	99%	99%	98%	95%	93%	90%	86%	83%	79%	75%	70%	65%	59%	51%	44%	36%	29%	22%	18%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2000	2006	1985	1958	1922	1866	1810	1739	1664	1588	1508	1428	1309	1184	1048	892	737	597	458	353
100%	100%	99%	98%	96%	93%	90%	87%	83%	79%	75%	71%	65%	59%	52%	45%	37%	30%	23%	18%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
2000	1986	1972	1956	1908	1860	1798	1727	1655	1575	1495	1398	1293	1178	1027	877	728	580	448	361
100%	99%	99%	98%	95%	93%	90%	86%	83%	79%	75%	70%	65%	59%	51%	44%	36%	29%	22%	18%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
57°	86.6°	104.6°	97.2%	92.6%