

LIGHT LABORATORY, INC.

8165 E Kaiser Blvd. Anaheim, CA 92808

SHT 1 OF 7

Test #: L07110601

Date: 7/26/2011

Luminaire Photometric Performance LM-79-2008

Manufacturer:	CALIFORNIA ACCENT LIGHTING
Model Number:	LPL8150/2W/LED-WW

Total Lumens:	211.79
Input Power (W):	3.64
Input Current (Amp):	0.30
Input Power Factor:	N.A.
Efficacy: 58.18	
Color Rendering Index (CRI):	81.40
Correlated Color Temperature (K):	2937
Chromaticity Ordinate x:	0.441
Chromaticity Ordinate y:	0.405

*Test data documentation on file and available upon request.

*All results in accordance to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.

A					JS	7/26/11
REV.	LOG NUMBER	REVISION DESCRIPTION	REVISION BY	CHECKED BY	APPROVED BY	DATE




IES INDOOR REPORT
PHOTOMETRIC FILENAME : L07110601.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] L07110601
[TESTLAB] LIGHT LABORATORY, INC.
[ISSUEDATE] 7/26/2011
[MANUFAC] CALIFORNIA ACCENT LIGHTING
[LUMCAT] LPL8150/2W/LED-WW
[LUMINAIRE] 35-13/32"L. X 11/16"W. X 7/32"H. LED STRIP
[MORE] 18 MODULES, EACH MODULE HAS 3 WARM WHITE LEDS WITH 21/32" LED SPACING
[MORE] TOTAL 54 LEDS, LED STRIP IS ON ALUMINUM CHANNEL
[LAMPPOSITION] 0,0
[LAMPCAT] WARM WHITE LED
[OTHER] INDICATING THE CANDELA VALUES ARE ABSOLUTE AND
[MORE] SHOULD NOT BE FACTORED FOR DIFFERENT LAMP RATINGS.
[POWER SUPPLY] 12VDC CONSTANT VOLTAGE SOURCE
[INPUT] 12VDC, 3.64W
[TEST PROCEDURE] IESNA:LM-79-08

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	212
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	58
Total Luminaire Watts	3.64
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.24
Spacing Criterion (90-270)	1.24
Spacing Criterion (Diagonal)	1.36
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	2.90 ft
Luminous Width (90-270)	0.01 ft
Luminous Height	0.00 ft



IES INDOOR REPORT
PHOTOMETRIC FILENAME : L07110601.IES

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	26169	25906	26011
55	24891	24761	24632
65	22638	22550	22199
75	18339	18196	17909
85	11913	12764	12339

IES INDOOR REPORT
PHOTOMETRIC FILENAME : L07110601.IES

CANDELA TABULATION

	<u>0.0</u>	<u>22.5</u>	<u>45.0</u>	<u>67.5</u>	<u>90.0</u>
0	77.7	77.7	77.7	77.7	77.7
5	76.9	77.0	77.2	77.2	77.0
10	76.0	75.9	75.8	76.0	76.1
15	74.0	74.1	73.9	74.1	74.0
20	71.4	71.3	71.2	71.4	71.3
25	68.6	68.1	68.2	68.1	68.3
30	64.3	64.3	64.2	64.1	64.4
35	60.1	59.9	59.7	59.8	59.9
40	55.0	55.1	54.8	54.6	54.9
45	49.9	49.4	49.4	49.4	49.6
50	44.0	43.8	43.7	43.5	43.5
55	38.5	38.5	38.3	38.1	38.1
60	32.4	32.3	32.1	32.0	31.9
65	25.8	25.8	25.7	25.5	25.3
70	19.4	19.4	19.2	19.2	18.9
75	12.8	12.8	12.7	12.7	12.5
80	7.0	7.1	7.0	6.9	6.8
85	2.8	3.0	3.0	2.9	2.9
90	0.0	0.0	0.0	0.0	0.0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : L07110601.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-30	59.59	N.A.	28.10
0-40	97.01	N.A.	45.80
0-60	169.26	N.A.	79.90
0-90	211.79	N.A.	100.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
0-180	211.79	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	7.32
10-20	20.87
20-30	31.40
30-40	37.41
40-50	38.15
50-60	34.11
60-70	25.41
70-80	13.62
80-90	3.50
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : L07110601.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	109	104	100	96	106	102	98	95	98	94	92	94	91	89	90	88	86	84
2	99	91	84	78	96	89	83	78	85	80	76	82	78	74	79	76	72	70
3	90	80	72	65	88	78	71	65	75	69	64	73	67	62	70	65	61	59
4	83	71	62	55	80	69	61	55	67	60	54	65	59	54	62	57	53	51
5	76	63	54	48	74	62	54	47	60	53	47	58	52	46	56	51	46	44
6	70	57	48	42	68	56	48	42	54	47	41	53	46	41	51	45	40	38
7	65	52	43	37	63	51	43	37	49	42	36	48	41	36	47	41	36	34
8	61	47	39	33	59	47	38	33	45	38	33	44	37	32	43	37	32	30
9	57	43	35	30	55	43	35	30	42	34	29	41	34	29	40	33	29	27
10	53	40	32	27	52	39	32	27	38	32	27	38	31	27	37	31	26	25

POLAR GRAPH



Maximum Candela = 77.7 Located At Horizontal Angle = 0, Vertical Angle = 0
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.) : BLUE
2 - Vertical Plane Through Horizontal Angles (90 - 270) : MAGENTA
3 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.) : RED