


Light efficiency:**65 Lumen/Watt****Light quality:****CRI: 93.9****Color temperature:****3091 K****Output: 915 lm****Peak: 2691 cd****Power: 14.0 W****Voltage: 120 V****Current: 0.117 A****PF: 0.9****THD: n/a %****Product name:****H2x-1030N00xxN-xxx - 2****Driver Used:****Test Date:****2019-08-22****Beam Angle:****35.6°****Field Angle:****69.2°****Cut Off Angle:****117.6°****Beam details**

*measured at center of beam

Mounting Height (feet)\(meter)	Lux*	Footcandles*	Beam width (feet) / (meter)
4 ft / 1.2 m	302 lx	28 fcd	2.6 ft / 0.8 m
8 ft / 2.4 m	75 lx	7 fcd	5.1 ft / 1.6 m
12 ft / 3.7 m	34 lx	3 fcd	7.7 ft / 2.3 m
16 ft / 4.9 m	19 lx	2 fcd	10.3 ft / 3.1 m
20 ft / 6.1 m	12 lx	1 fcd	12.8 ft / 3.9 m


Beam center

Light planning Photometric Testing Report

Zonal Lumen Summary

Zone	Lumen	%Luminaire
0-30	483	52.79%
0-40	742	81.09%
0-60	847	92.57%
60-90	40.7	4.45%
70-100	24.2	2.64%
90-120	12.4	1.36%
0-90	888	97.05%
90-180	26.5	2.90%
0-180	915	100.00%

ISO lux diagram



Mounting height: 3.05 meters (10 feet)

Lux at center:	48 lx
3%	1.44 lx
5%	2.40 lx
10%	4.80 lx
30%	14.40 lx
50%	24.00 lx


Conditions:
Number of planes: 16
Lux distribution on a surface when lamp is mounted at 3.05 meters from the surface.

Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	118	118	118	118	115	115	115	115	110	110	110	104	104	104	99	99	99	97
1	111	108	105	102	109	106	103	100	101	99	97	97	95	93	93	91	90	88
2	105	99	94	90	102	97	92	89	93	89	86	89	87	84	86	84	82	80
3	98	91	85	80	96	89	83	79	86	81	77	83	79	76	80	77	74	72
4	92	83	77	72	90	82	76	71	79	74	70	77	72	69	74	71	68	66
5	86	77	70	65	84	75	69	64	73	68	63	71	66	63	69	65	62	60
6	81	71	64	59	79	70	63	59	68	62	58	66	61	57	65	60	57	55
7	76	66	59	54	75	65	58	54	63	57	53	62	56	53	60	56	52	50
8	72	61	54	49	70	60	54	49	59	53	49	57	52	48	56	51	48	46
9	68	57	50	45	66	56	50	45	55	49	45	54	48	45	53	48	44	43
10	64	53	46	42	63	52	46	42	51	46	42	50	45	41	49	44	41	40



LAMPS (number of lamps)

Luminaire budgetary diagram




Color details


Photometric Testing Report



TM30: 90.8



CRI: 93.9 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
95.1	96.0	93.9	94.2	93.4	93.5	95.6	89.7	74.9	87.8	93.0	76.7	95.3	95.5	93.6


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
92.5	93.3	89.1	92.6	91.6	94.7	93.3	96.0	92.9	84.6	83.7	89.1	93.5	89.5	91.2	86.8

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
92.6	97.3	85.6	85.2	89.7	91.3	89.8	92.6	95.8	92.2	91.7	92.9	94.1	91.5	91.7

CQS: 90.9



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3091 K	93.9	74.9	90.8	100.5	90.9	0.429	0.399	0.248	0.345	-0.0010

UGR Photometric Testing Report

Glare Evaluation According to UGR

p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	15.4	16.2	15.7	16.4	16.7	28.6	29.4	28.9	29.6	29.9
	3H	16.4	17.1	16.7	17.4	17.7	28.4	29.1	28.8	29.4	29.7
	4H	16.8	17.5	17.2	17.8	18.1	28.3	29.0	28.7	29.3	29.6
	6H	17.3	17.9	17.7	18.3	18.6	28.3	28.9	28.6	29.2	29.6
	8H	17.6	18.2	17.9	18.5	18.9	28.2	28.8	28.6	29.2	29.5
	12H	17.8	18.4	18.2	18.7	19.1	28.2	28.8	28.6	29.1	29.5
4H	2H	16.0	16.7	16.3	17.0	17.3	28.3	29.0	28.7	29.3	29.6
	3H	17.2	17.8	17.6	18.1	18.5	28.2	28.8	28.6	29.1	29.5
	4H	17.8	18.3	18.3	18.7	19.1	28.1	28.6	28.5	29.0	29.4
	6H	18.4	18.9	18.9	19.3	19.7	28.1	28.5	28.5	28.9	29.3
	8H	18.8	19.1	19.2	19.6	20.0	28.0	28.4	28.5	28.8	29.3
	12H	19.1	19.4	19.6	19.9	20.4	28.0	28.3	28.5	28.8	29.3
8H	4H	18.3	18.7	18.7	19.1	19.5	28.0	28.4	28.5	28.8	29.3
	6H	19.0	19.3	19.5	19.8	20.3	27.9	28.2	28.4	28.7	29.2
	8H	19.5	19.7	20.0	20.2	20.7	27.9	28.2	28.4	28.7	29.2
	12H	19.9	20.1	20.4	20.6	21.2	27.9	28.1	28.4	28.6	29.2
12H	4H	18.3	18.7	18.8	19.1	19.6	28.0	28.3	28.4	28.7	29.2
	6H	19.2	19.4	19.7	19.9	20.5	27.9	28.1	28.4	28.6	29.2
	8H	19.7	19.9	20.2	20.4	20.9	27.9	28.1	28.4	28.6	29.2
Variation of the observer position for the luminaire distance S											
S = 1.0H		+1.1 / -0.4					+5.4 / -11.2				
S = 1.5H		+0.4 / -0.4					+8.2 / -11.9				
S = 2.0H		+0.6 / -0.7					+10.2 / -12.3				
Standard table		BK06					BK00				
Correction summand		2.3					10.0				
Corrected glare indices referring to 915 lm total luminous flux											

Due to our continued efforts to improve our products, product specifications are subject to change without notice. Please refer to our website for the latest test results.