

Light efficiency:

69 Lumen/Watt

Light quality:

CRI: 82.5

Color temperature:

2926 K

Output: 1333 lm

Peak: 1969 cd

Power: 19.5 W

PF: 0.99



Beam angle


55.6°

Product name:

608-3-XTM19-20LM-30K-83-SA60-CLR

Date and time:

9/26/2016 4:11:59 PM




CIE 1931



x: 0.436

y: 0.393


Spectra




Color details



TM30: 77.5



CRI: 82.5 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
81.4	88.8	94.5	81.5	81.1	85.6	83.4	63.5	17.3	74.2	81.1	72.9	82.7	96.6	75.6

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
78.5	76.6	65.3	71.3	78.4	79.3	69.7	83.3	81.9	81.2	76.8	77.9	85.0	81.7	76.5	79.9

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	x	y	u	v	Δuv
2926 K	82.5	17.3	77.5	101.8	0.436	0.393	0.255	0.345	0.0044

TM30 details







Rf 77.5

Fidelity index Rf


Rg 101.8

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	79	-10%	-4%
2	77	-8%	9%
3	65	-1%	17%
4	71	10%	15%
5	78	14%	8%
6	79	12%	-4%
7	70	7%	-16%
8	83	-1%	-10%
9	82	-7%	-7%
10	81	-9%	1%
11	77	-6%	12%
12	78	5%	9%
13	85	9%	-1%
14	82	9%	-9%
15	76	4%	-13%
16	80	-6%	-13%



Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1969lx	492lx	219lx	123lx	79lx	55lx	40lx	31lx	24lx	20lx	16lx	14lx	12lx	10lx	9lx	8lx	7lx	6lx	5lx	5lx
182.9fcd	45.7fcd	20.3fcd	11.4fcd	7.3fcd	5.1fcd	3.7fcd	2.9fcd	2.3fcd	1.8fcd	1.5fcd	1.3fcd	1.1fcd	0.9fcd	0.8fcd	0.7fcd	0.6fcd	0.6fcd	0.5fcd	0.5fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1969	1962	1925	1789	1661	1598	1568	1548	1535	1571	1570	1511	1391	1210	967	672	408	218	103	41
100%	100%	98%	91%	84%	81%	80%	79%	78%	80%	80%	77%	71%	61%	49%	34%	21%	11%	5%	2%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1969	1950	1913	1815	1700	1632	1599	1570	1551	1584	1585	1521	1391	1202	956	668	402	216	108	45
100%	99%	97%	92%	86%	83%	81%	80%	79%	80%	81%	77%	71%	61%	49%	34%	20%	11%	6%	2%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1969	1962	1925	1789	1661	1598	1568	1548	1535	1571	1570	1511	1391	1210	967	672	408	218	103	41
100%	100%	98%	91%	84%	81%	80%	79%	78%	80%	80%	77%	71%	61%	49%	34%	21%	11%	5%	2%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1969	1950	1913	1815	1700	1632	1599	1570	1551	1584	1585	1521	1391	1202	956	668	402	216	108	45
100%	99%	97%	92%	86%	83%	81%	80%	79%	80%	81%	77%	71%	61%	49%	34%	20%	11%	6%	2%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
55.6°	68.6°	75.6°	98.6%	97.9%