

Light efficiency:

67 Lumen/Watt

Light quality:

CRI: 82.5

Color temperature:

2944 K

Output: 1308 lm

Peak: 1521 cd

Power: 19.4 W

PF: 0.99



Beam angle


59.1°

Product name:

608-3-XTM19-20LM-30K-83-DA60-CLR

Date and time:

9/27/2016 11:00:06 AM




CIE 1931



x: 0.434

y: 0.392


Spectra




Color details



TM30: 77.7



CRI: 82.5 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
81.5	88.9	94.5	81.4	81.2	85.6	83.3	63.6	17.5	74.4	80.9	73.1	82.8	96.7	75.8

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
78.7	76.5	65.2	71.7	78.7	79.5	70.4	83.6	82.4	81.3	76.6	77.9	85.1	81.6	76.8	79.7

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	x	y	u	v	Δuv
2944 K	82.5	17.5	77.7	101.7	0.434	0.392	0.254	0.344	0.0047

TM30 details







Rf 77.7

Fidelity index Rf


Rg 101.7

Gamut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	79	-10%	-3%
2	77	-8%	9%
3	65	-1%	17%
4	72	9%	15%
5	79	14%	8%
6	80	12%	-3%
7	70	7%	-16%
8	84	-1%	-9%
9	82	-7%	-6%
10	81	-9%	2%
11	77	-6%	12%
12	78	5%	9%
13	85	9%	0%
14	82	9%	-9%
15	77	4%	-12%
16	80	-6%	-13%



Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
1521lx	380lx	169lx	95lx	61lx	42lx	31lx	24lx	19lx	15lx	13lx	11lx	9lx	8lx	7lx	6lx	5lx	5lx	4lx	4lx
141.3fcd	35.3fcd	15.7fcd	8.8fcd	5.7fcd	3.9fcd	2.9fcd	2.2fcd	1.7fcd	1.4fcd	1.2fcd	1fcd	0.8fcd	0.7fcd	0.6fcd	0.6fcd	0.5fcd	0.4fcd	0.4fcd	0.4fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1521	1516	1501	1475	1439	1396	1346	1287	1227	1168	1111	1057	1002	936	851	731	591	449	318	217
100%	100%	99%	97%	95%	92%	88%	85%	81%	77%	73%	69%	66%	62%	56%	48%	39%	30%	21%	14%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1521	1517	1503	1480	1447	1407	1359	1302	1241	1182	1125	1069	1012	946	854	734	597	458	330	229
100%	100%	99%	97%	95%	93%	89%	86%	82%	78%	74%	70%	67%	62%	56%	48%	39%	30%	22%	15%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1521	1516	1501	1475	1439	1396	1346	1287	1227	1168	1111	1057	1002	936	851	731	591	449	318	217
100%	100%	99%	97%	95%	92%	88%	85%	81%	77%	73%	69%	66%	62%	56%	48%	39%	30%	21%	14%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
1521	1517	1503	1480	1447	1407	1359	1302	1241	1182	1125	1069	1012	946	854	734	597	458	330	229
100%	100%	99%	97%	95%	93%	89%	86%	82%	78%	74%	70%	67%	62%	56%	48%	39%	30%	22%	15%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
59.1°	80.8°	106.8°	98.1%	93.6%