

Light efficiency:

88 Lumen/Watt

Light quality:

CRI: 79.7

Color temperature:


2905 K

Output: 2161 lm

Peak: 1461 cd

Power: 24.6 W

PF: 1.0



Beam angle


72.6°

Product name:

NU3-QW-XTM19-27LM-30K-83-WW-120-DIM10-NC-WH-WH


Date and time:

12/21/2017 2:26:01 PM





CIE 1931
x: 0.449
y: 0.417


Spectra




Color details



TM30: 79.1



CRI: 79.7 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
77.1	85.3	93.5	79.6	76.3	80.6	84.7	60.1	5.6	66.7	77.6	62.9	78.2	96.0	69.9

TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
76.3	76.7	69.6	76.2	83.1	85.4	73.5	86.3	81.6	79.9	77.3	80.5	86.8	81.6	76.4	78.9

Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	x	y	u	v	Δuv
2905 K	79.7	5.6	79.1	97.7	0.449	0.417	0.253	0.352	0.0033

TM30 details







Rf 79.1

Fidelity index Rf


Rg 97.7

Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	76	-11%	-4%
2	77	-9%	7%
3	70	-3%	14%
4	76	7%	13%
5	83	10%	7%
6	85	8%	-3%
7	74	3%	-15%
8	86	-3%	-7%
9	82	-8%	-5%
10	80	-10%	3%
11	77	-7%	12%
12	81	3%	7%
13	87	7%	-2%
14	82	6%	-11%
15	76	2%	-13%
16	79	-8%	-13%



Beam details



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
933lx	233lx	104lx	58lx	37lx	26lx	19lx	15lx	12lx	9lx	8lx	6lx	6lx	5lx	4lx	4lx	3lx	3lx	3lx	2lx
86.7fcd	21.7fcd	9.6fcd	5.4fcd	3.5fcd	2.4fcd	1.8fcd	1.4fcd	1.1fcd	0.9fcd	0.7fcd	0.6fcd	0.5fcd	0.4fcd	0.4fcd	0.3fcd	0.3fcd	0.3fcd	0.2fcd	0.2fcd

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
933	937	937	939	936	922	889	834	754	641	498	348	211	119	73	47	27	12	5	0
100%	100%	100%	101%	100%	99%	95%	89%	81%	69%	53%	37%	23%	13%	8%	5%	3%	1%	1%	0%

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
933	1072	1211	1336	1424	1453	1415	1315	1168	969	742	522	306	142	70	43	24	9	3	0
100%	115%	130%	143%	153%	156%	152%	141%	125%	104%	80%	56%	33%	15%	8%	5%	3%	1%	0%	0%

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
933	927	921	910	885	841	773	680	554	409	268	154	91	60	38	18	8	2	0	0
100%	99%	99%	98%	95%	90%	83%	73%	59%	44%	29%	17%	10%	6%	4%	2%	1%	0%	0%	0%

Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
933	799	675	565	477	415	370	319	257	192	145	112	87	65	41	20	10	1	0	0
100%	86%	72%	61%	51%	44%	40%	34%	28%	21%	16%	12%	9%	7%	4%	2%	1%	0%	0%	0%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
72.6°	122.4°	150°	92.3%	69.3%