

Light efficiency:

80 Lumen/Watt

Light quality:

CRI: 81.0

Color temperature:

3092 K

Output: 3251 lm

Peak: 6048 cd


Power: 40.7 W

PF: 0.98



NU3-RD-SW-40LM-30K-80-40C-NL-120-DIM10-NC-WH-WH

Date and time:
11/9/2020 2:29:12 PM




Beam angle

38.9°






CIE 1931
x: 0.431
y: 0.403

Spectra




Power






TM30: 83.1



CRI: 81.0 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
79.0	88.2	95.8	79.7	78.6	84.7	83.5	58.9	3.1	72.5	78.1	66.0	80.9	97.6	71.3


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
79.2	79.6	74.4	84.2	90.6	90.4	84.4	91.1	88.4	80.4	77.9	86.0	88.4	81.4	78.6	78.7

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
76.5	96.3	79.4	76.9	80.3	80.3	80.7	84.8	96.1	86.7	83.5	81.6	81.0	69.4	71.7

CQS: 80.2



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3092 K	81.0	3.1	83.1	96.9	80.2	0.431	0.403	0.247	0.347	0.0004







Rf 83.1


Fidelity index Rf

Rg 96.9

Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	79	-12%	-1%
2	80	-9%	8%
3	74	-3%	13%
4	84	3%	10%
5	91	5%	5%
6	90	5%	-3%
7	84	-1%	-10%
8	91	-4%	-4%
9	88	-7%	1%
10	80	-7%	9%
11	78	-2%	15%
12	86	7%	5%
13	88	6%	-4%
14	81	7%	-13%
15	79	-1%	-14%
16	79	-7%	-16%





Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
6048lx	1512lx	672lx	378lx	242lx	168lx	123lx	94lx	75lx	60lx	50lx	42lx	36lx	31lx	27lx	24lx	21lx	19lx	17lx	15lx
561.8fc	140.5fc	62.4fcd	35.1fcd	22.5fcd	15.6fcd	11.5fcd	8.8fcd	6.9fcd	5.6fcd	4.6fcd	3.9fcd	3.3fcd	2.9fcd	2.5fcd	2.2fcd	1.9fcd	1.7fcd	1.6fcd	1.4fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
6048	6048	5944	5783	5571	5183	4795	4306	3793	3318	2907	2495	2212	1934	1697	1494	1285	1033	782	556
100%	100%	98%	96%	92%	86%	79%	71%	63%	55%	48%	41%	37%	32%	28%	25%	21%	17%	13%	9%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
6048	6048	5944	5783	5571	5183	4795	4306	3793	3318	2907	2495	2212	1934	1697	1494	1285	1033	782	556
100%	100%	98%	96%	92%	86%	79%	71%	63%	55%	48%	41%	37%	32%	28%	25%	21%	17%	13%	9%

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
6048	6048	5944	5783	5571	5183	4795	4306	3793	3318	2907	2495	2212	1934	1697	1494	1285	1033	782	556
100%	100%	98%	96%	92%	86%	79%	71%	63%	55%	48%	41%	37%	32%	28%	25%	21%	17%	13%	9%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
6048	6048	5944	5783	5571	5183	4795	4306	3793	3318	2907	2495	2212	1934	1697	1494	1285	1033	782	556
100%	100%	98%	96%	92%	86%	79%	71%	63%	55%	48%	41%	37%	32%	28%	25%	21%	17%	13%	9%

Beam angle 50°	Field angle 10°	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
{B_ANG}°	75.1°	84.9°	99.4%	99.0%