



FEATURES:

- ✓ Architectural luminaire with direct or direct-indirect distribution.
- ✓ Light source: LED board (5.5"/11"/22"/24").
- ✓ Diffused illumination is provided by high efficiency frosted opal lens.
- ✓ Sleek body of the luminaire combines two aluminum side with laser cut metal top enclosure.
- ✓ Suitable for suspended and wall mounted installations.
- ✓ Extruded aluminum body comes with white, black or grey finishes.
- ✓ Also available with custom color options or vinyl decals.
- ✓ LED Strips are rated for 60,000hrs. L80 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SIZE

- ☐ 2 Feet
- ☐ 3 Feet
- ☐ 4 Feet
- ☐ 5 Feet
- ☐ *

*Specify required Size.

SOURCE

- ☐ 25WLED
- ☐ 50WLED
- ☐ 75WLED*

*Available for 4 & 5 Feet.
 **Other Wattages are available.

RADIANCE

- ☐ DD - Direct (100%Down)
- ☐ ID - Indirect (100%Up)**
- ☐ UD - Uneven(70%Down/30%Up)**

*Light Distribution.
 **Suspended Configuration only.

VOLTAGE

- ☐ 120V
- ☐ 277V
- ☐ 347V*

*Not available for all configurations.

DRIVER

- ☐ ST - Standard
- ☐ DL - 0-10V Dimming (1%)
- ☐ DA - DALI
- ☐ *

* Please specify dimming method (ELV).

MOUNTING

- ☐ S4-Suspension 4Feet
- ☐ S6-Suspension 6Feet
- ☐ S Feet*
- ☐ C4-Canopy 4Feet
- ☐ C6-Canopy 6Feet
- ☐ C Feet*
- ☐ WM - Wall Mount
- ☐ SF - Surface Mount

*Please specify required Length.

LENS

- ☐ OP - Opal

FINISH

- ☐ WH - White
- ☐ BK - Black
- ☐ GR - Grey
- ☐ CF - Custom RAL#
- ☐ VD - Vinyl Decal*

* Please provide 600dpi Image.

CCT

- ☐ 30K - 3000Kelvin
- ☐ 35K - 3500Kelvin
- ☐ 40K - 4000Kelvin
- ☐ TW - Tunable White** (2700K-6500K)

*Other options are available.
 **Available with Dali controls.

OPTIONS

- ☐ No Options*
- ☐ 90 CRI
- ☐ DS-Daylight Sensor
- ☐ DC - Dual Circuit**
- ☐ OS - Occupancy Sensor
- ☐ DOS - Daylight & Occupancy Sensor

*Leave Empty.
 **Down /Up Control separately.
 ***Combination example (90CRI/DS).

LUMEN OUTPUT:

Watts	30K	35K	40K
25W	2205 lm	2250 lm	2295 lm
50W	4410 lm	4500 lm	4590 lm
75W	6610 lm	6750 lm	6890 lm

Project:

Type:



SPECIFICATION:

ED RING+

SIZE	SOURCE	RADIANCE	VOLTAGE	DRIVER	MOUNTING	LENS	FINISH	CCT	OPTIONS
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Enter the Product Code into the boxes above.

SIZE:



Size	Diameter
2 Feet	23.60 Inch
3 Feet	35.40 Inch
4 Feet	47.20 Inch
5 Feet	59.00 Inch

RADIANCE:

DIRECT DISTRIBUTION



UNEVEN DISTRIBUTION



MOUNTING:




SUSPENDED - STRAIGHT WIRE



SUSPENDED - CEILING CANOPY



SURFACE MOUNT



WALL MOUNT