

## FEATURES:

- ✓ Architectural luminaire with direct or indirect distribution.
- ✓ Light source: LED board (5.5"/11"/22"/24").
- ✓ Diffused illumination is provided by high efficiency frosted opal lens.
- ✓ Suitable for surface, suspended and recessed installations.
- ✓ Extruded aluminum body comes with white, black or grey finishes.
- ✓ Also available with custom color options or vinyl decals.
- ✓ LED Strips are rated for 60,000hrs. L80 with +85 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

### SIZE

- ☐ 2x2x2 Feet  
☐ 3x3x3 Feet  
☐ 4x4x4 Feet  
☐ \*

\* Specify required length.  
 \*\* Custom angles are available.

### VOLTAGE

- ☐ 120V  
☐ 277V  
☐ 347V\*

\*Not available for all configurations.

### MOUNTING

- ☐ S4-Suspension 4Feet  
☐ S6-Suspension 6Feet  
☐ S  Feet\*  
☐ WM - Wall Mount  
☐ SF - Surface Mount  
☐ RT - Recessed Trimless

\*Please specify required Length.

### CCT

- ☐ 30K - 3000Kelvin  
☐ 35K - 3500Kelvin  
☐ 40K - 4000Kelvin  
☐ TW - Tunable White\*\* (2700K-6500K)

\*Other options are available.  
 \*\*Available with Dali controls.

### SOURCE

- ☐ 25WLED  
☐ 50WLED  
☐ 75WLED\*

\* Available for 3 & 4 Feet.

### DRIVER

- ☐ ST - Standard  
☐ DL - 0-10V Dimming (1%)  
☐ DA - DALI  
☐ \*

\* Please specify dimming method (ELV).

### LENS

- ☐ OP - Opal

### FINISH

- ☐ WH - White  
☐ BK - Black  
☐ GR - Grey  
☐ CF - Custom  RAL#  
☐ VD - Vinyl Decal\*

\* Please provide 600dpi Image.

### OPTIONS

- ☐ No Options\*  
☐ 90 CRI  
☐ DS-Daylight Sensor  
☐ DC - Dual Circuit\*\*  
☐ OS - Occupancy Sensor  
☐ DOS - Daylight & Occupancy Sensor

\*Leave Empty.  
 \*\*Down /Up Control separately.  
 \*\*\*Combination example (90CRI/DS).

### RADIANCE

- ☐ DD - Direct (100%Down)  
☐ ID - Indirect (100%Up)\*\*

\*Light Distribution.  
 \*\*Suspended Configuration only.

### LUMEN OUTPUT:

Watts	30K	35K	40K
25W	2610 lm	2650 lm	2690 lm
50W	5150 lm	5250 lm	5380 lm
75W	7720 lm	7875 lm	8030 lm

Project:

Type:



### SPECIFICATION:

**ED TRIAD+**

SIZE	SOURCE	RADIANCE	VOLTAGE	DRIVER	MOUNTING	LENS	FINISH	CCT	OPTIONS
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Enter the Product Code into the boxes above.

## SIZE:



Size	L x W
2x2x2 Feet	34.706 x 40.056 Inch
3x3x3 Feet	51.206 x 59.105 Inch
4x4x4 Feet	67.706 x 78.154 Inch


## RADIANCE:

### DIRECT DISTRIBUTION


### INDIRECT DISTRIBUTION



## MOUNTING:




SURFACE MOUNT



SUSPENDED



WALL MOUNT



RECESSED TRIMLESS