
100 Linear Surface Mount

Straight Run Submittal





4" 100mm

		1 1				10#				
Ordering Information										
WG-100LDL	SM									
Model	Fixation	Pattern	Length	Power ²	CRI∕ CCT³	Driver ⁴	Lens	Finish		
WG-100LDL	SM	S	A AxB AxBxC AxBxAxB	L M H	927 930 935 940	X S D010 L3DAE L3D0E DFPN	OD (std) SD	W (std) B G F		

Luminaire

- Surface ceiling mount.
- Easily installed internal LED tray assembly with integral driver.
- High reflectance white reflector.
- Flush snap-in opal diffuser (standard).
- Powdercoat painted white RAL 9010.

Fixation

■ SM = Surface Mount

Pattern

- S = Straight run
- P = Standard patterns 2, 3 or 4 sided with 90° corners on the same plane¹
- PZ = Non-standard patterns and/or corners other than 90° on multiple planes, consult factory¹

Length

 A, B, C = specify inches to the nearest 0.25" (i.e. 72.25"). For pattens specify each length (i.e. 2 sided: A x B = 72.25" x 48"; 3 sided: A x B x C; 4 sided: A x B x A x B).

Power²

- L = 3.2W/ft low power (24V)
- M = 6.4W/ft mid power (24V)
- H = 10.5W/ft mid power (24V)

CRI/CCT³

90+ CRI (low/mid/high power)

- 927 = 2700K, (173/321/478 lm/ft)
- 930 = 3000K, (179/331/493 lm/ft)
- 935 = 3500K, (183/337/503 lm/ft)
- 940 = 4000K, (184/341/508 lm/ft)

Customer Approval	Company
Approved	Signature
Approved with corrections noted	Print Name
Revise and Resubmit	Date

Original Date Submitted

Driver (Integral)⁴

- X = No driver, ordered separately
- S = Standard driver 120-277V
- D010 = Osram, 10%, 0-10V dimming, 120-277V
- L3DAE = Lutron Hi-lume 1% EcoSystem, 120-277V
- L3D0E = Lutron Hi-lume Premier 0.1 EcoSystem, 120-277V
- DFPN = Lutron Forward Phase 1% 120VAC

Lens

- OD = Satin opal diffuser (standard)
- SD = Satin clear diffuser (high efficiency)

Finish

- W = White, 20% gloss, RAL9010 (standard)
- B = Black, 20% gloss
- G = Gray, 20% gloss
- F = Custom finished trim, specify RAL

Emergency

- Emergency LED driver available, order separately.
- ¹ See pattern specsheet.
- ² Wattage shown does not include power supplies/drivers.
- $^{\scriptscriptstyle 3}$ Delivered lumens with satin opal diffuser shown.
- ⁴ Remote power supply required. See power supply page for details.



Project Name Fixture Type

PO#

100 Linear Surface

100 Linear Surface			inter•lux					
Submittal - Straight Run			Pr	Project Name				
				Fix	ture Type		PO#	
System 1	-			Cu	ıstomer Approval	Company _		
2					Approved	Signature		
-					Approved with corrections noted	Print Name		
4					Revise and Resubmit	Date		
5								
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
		ntrol feed trance	Note: 50' per power power feed entrance	maximum r feed opal acr	'A'			