

# **Edgeless Cove LED**

## Submittal - Pattern 4 Sided Raft







Fixture Type							PO#		
Ordering Information									
WG-EC	PR							Р	
Model	Туре	Length	LED <sup>3</sup>	Color	Voltage	Power	Diffuser	Moun	
WG-EC	PR <sup>2</sup>	AxBxAxB	L	827	UNV	S	S (STD)	Р	

120

830

835

940

### Luminaire

- Indirect cove system featuring plaster-in precision knife edge for clean, minimal effect.
- White LED light source.
- Lengths and angles factory cut to exact field dimensions.
- Powder coat painted white RAL 9010.
- Snap-on satin diffuser optimized for forward distribution (standard).

#### Type

PR = Standard patterns raft 2, 3 or 4 sided with 90° corners<sup>2</sup>

#### Length

- A, B, C = specify feet & inches to the
- nearest 0.25" (i.e. 6' 5.5")

#### LED<sup>3</sup>

- L = Low Power (3W/ft)
- M = Mid Power (6W/ft)
- H = High Power (10W/ft)

#### Color / Lumens

- 80+ CRI minimum
- 827 = 2700K
- 830 = 3000K
- 835 = 3500K
- 840 = 4000K
- For 90+ CRI specify 927, 930, etc

Customer Approval	Company
Approved	Signature
Approved with corrections noted	Print Name
Revise and Resubmit	Date

**Original Submission Date** 

#### UNV = 120-277V ■ 120 = 120V (DFPN only)

D010

D3W

DES

DFPN

Voltage

OF

SF

#### Power Supply (integral)

- S = Standard driver, 120-277V
- D010 = Osram, 10%, 0-10V dimming, 120-277V
- D3W = Lutron, 1%, 3-wire fluorescent dimming, 120-277V
- DES = Lutron, 1%, EcoSystem E1/E2 digital dimming, 120-277V
- DFPN = Lutron 1% forward phase with neutral, 120V only

#### Diffuser

- S = Snap-on satin diffuser (standard)
- OF = Opal flat diffuser
- SF = Satin flat diffuser

#### Mounting

■ P = Plaster-in

#### Options<sup>2</sup>

Contact factory for emergency . lighting options

- 1 Standard setup assumes the cove ends at a perpendicular wall and the led board is set back from the end to minimize light on the perpendicular wall. Contact us for options.
- 2 See pattern specsheet.
- 3 Wattage shown does not include power supplies/drivers.



1



Options

Project Name

Μ

Н

## **Edgeless Cove LED**



Submittal - Pattern 4 Sided Raft PO#\_\_\_\_\_ Fixture Type **Overall Length** System Qty. **'B' 'A'** Customer Approval Company 1 Approved Signature 2 Approved with Print Name corrections noted 3 **Revise and Resubmit** Date \_ 4 \* overall length of finished mounting surface 90 deg. 90 deg. overalllength\* straight sections outside corner outside corner 'A' 'raft' 'raft' Light Direction housing housing housing Light Direction gear tray gear tray gear tray wall gear tray housing housing gear tray Light Direction wall overall length\* 'Β̈́ wall straight sections straight sectionsgear tray housing gear tray housing control feed entrance Note: 50' maximum per power feed \_ \_ \_ \_ \_ \_ power feed Drilled to fit in field entrance gear tray housing gear tray housing wall gear tray gear tray gear tray housing housing housing 90 deg. 90 deg. straight sections \_ Light Direction outside corner outside corner 'raft' 'raft'

410 381 1497 inter-lux.com answers@inter-lux.com Inter-lux reserves the right to make technical changes without notice.



2