

10 DAY SHIPPING

PAL

ARCHITECTURAL

QUICKSHIP



Qty: Type:

Project Name:

Catalog Number:

ORDERING GUIDE

- - - - - -

Series	Outputs	Color Temp. (CCT)	Color Render	Fixture Length	Ceiling Type - (Recessed)
MLR3 ⁴ Microlinea Recessed Series 3	MLR3 and MLS3-D: HO High Output ----- 746 Lms/Ft	K30 3000 Kelvin K35 3500 Kelvin	80 80 CRI	4' 4 Ft 8' 8 Ft	FT Flush Tile Clg. - 15/16" or 9/16" Grid TT Tegular Tile Clg. - 15/16" or 9/16" Grid
MLS3-D Microlinea Suspended & Ceiling Mt. Series 3 - Direct	MO Medium Output - 463 Lms/Ft	K40 4000 Kelvin			SG Screw Slot Grid Clg. OF Drywall Clg. - Overlap Flange
MLS3-I/D Microlinea Suspended Mount Series 3 - Indirect/Direct	MLS3-I/D: HO/HO High Output Up & Down -- 1624 Lms/Ft (Total) MO/MO Medium Output Up & Down -- 1029 Lms/Ft (Total)				Blank Leave blank if Suspended or Ceiling Mount fixture

- - -

Mountings	Lens - Indirect (Suspended)	Lens - Direct (All Fixture Types)	Finish - (Suspend & Ceiling)
RECESSED MOUNT	FDC Frosted Acrylic Dust Cover - (Snap-in)	LOH LED Optimized Acrylic Snap-in Lens - (Standard Distribution)	F01M Matte White (Standard) Blank Leave blank if Recessed fixture
TR 1/4-20 Threaded Rod - Overlap Flange-(By Others)			
YK Snap-In Yoke - Overlap Flange	Blank Leave blank if Direct-Only fixture		
AC Adjustable Cable Assy - Overlap Flange			
Blank Leave blank if Grid ceiling type			
SUSPENDED MOUNT - DIRECT & INDIRECT/DIRECT			
CN Adjustable Cable Assy (Non Tbar) - 36" Standard			
CEILING MOUNT			
J Ceiling Mount (Flush)			

- -

Voltage	Drivers - Dimming ^{2,3}	Emergency & Rating Options
120 120V	DIM0 Dimming 100% to 0%	EBPHST Emergency Battery Pack - 10 Watt ⁵ Self-Testing. (Integral Mount)
277 277V	DIM1 Dimming 100% to 1%	
UNV Universal Voltage (120V thru 277V)	DIM5 Dimming 100% to 5% DIM10 Dimming 100% to 10%	CP Chicago Plenum Listing



Fixture Notes:

- All fixtures are factory pre-wired for a single circuit.
- Unless otherwise requested, all fixtures contain integral-mount "power-on-board" drivers.
- Standard power supply (driver) is UL/CUL recognized, and available with 0-10V dimming capability & 120 - 277 universal voltage.
- Standard emergency battery pack is a 10 Watt constant power, self-testing, UL 924 listed pack from Iota Engineering - providing 1000 lumens of light for approximately 90 minutes. Battery packs are integral mounted.

Quick Ship Policy Notes:

- Quick Ship orders will ship within 10 working days. Ship dates do not include nationally recognized holidays. Orders received after 12:00 p.m. CST shall be dated as received on the following business day.
- Ship dates are contingent upon receipt of released, approved purchase order from a distributor with approved credit.
- Freight is allowed on shipments of \$7,500 or more to any one destination within the continental United States. Freight is allowed on shipments of \$10,000 or more to any one destination within Canada.
- Orders ship via standard motor freight. Any special or expedited shipping will require an additional surcharge.
- For more information, contact specs@pallighting.com.
- For orders of 250' or more, contact specs@pallighting.com.

