



INTENDED USE:

- For use in residential, commercial and hospitality markets
- For wall or vanity application
- Fixture is designed for optional up/ down directional lighting
- Baffle front cover plate is also removable for 180° illumination

PRODUCT FEATURES:

- Comes standard with multi-volt ballast
- Available in prismatic acrylic lens and white end caps
- Individually boxed
- Diffuser easily removed via locking nut at both ends of fixture
- Post-painted body and hemmed edges allow for safe handling and installation
- CEE qualified ballast comes standard on most fixture options (Consult factory for details)

OPTIONAL FEATURES:

- Dividers for up/downlight
- Front baffle cover available for light block

LISTING

UL/C-UL listed to US and Canadian standard

WARRANTY

Guaranteed for one year against mechanical defects

Ordering Information > Example: 1.5-OW2B-2-15-T8-MVOLT-EMG-T5-T5HO-700

1.5	OW2B								
FIXTURE SIZE	SERIES	WATTAGE	VOLTAGE	# OF BALLAST	BALLAST FACTOR	EMERGENCY BATTERY PACK OPTIONS (L. = LUMENS)			
1.5 - 18"	OW2B-Oracle Fluorescent Wall/Ceiling Bracket	18" FIXTURE 2-15-T8 (2 lamps/15W/T8)	(Blank) - MVOLT (120/277) 120 277 347	(Blank) - 1 Ballast 2 - 2 Ballasts	(Blank) - Normal BF HBF - High BF LBF - Low BF	ORDER CODE	DESCRIPTION		
						EMG-T8-BX-450	Up to 450 L. for T8 or BX		
						EMG-T8-BX-600	Up to 600 L. for T8 or BX		
						EMG-T8-BX-700	Up to 700 L. for T8 or BX		
						EMG-T8-BX-1400	Up to 1400 L. for T8 or BX		
						EMG-T5-T5HO-700	Up to 700 L. for T5 or T5HO		
						EMG-T5-T5HO-1300	Up to 1300 L. for T5 or T5HO		
						EMG-SD-T8-BX-T5-T5HO-1400	Self-Diagnostic 1400 L. for T8, BX, T5 or T5HO		
						EMG-ICE-T8-BX-T5-T5HO-1400	ICE Pack 1400 L. for T8, BX, T5 or T5HO		
						GTD	Generator Transfer Device		
						* 2' = For T8 only 450 L available * 2' = For T5 no emergency option available			
						WIRING OPTIONS	OTHER OPTIONS		
						FBF - Internal Fast Blow Fuse	INMS - Motion Sensor		
						SBF - Internal Slow-Blow Fuse	USA - Made in America Compliance		
						RIS - Radio Interference Suppressor			

BALLAST CONFIGURATION & CODE											
15W/T8	17W/T8	25W/T8	32W/T8	59W/T8	14W/T5	24W/T5HO	21W/T5	39W/T5HO	28W/T5	54W/T5HO	DESCRIPTION
(Blank)	(Blank)	-	(Blank)	(Blank)	-	-	-	-	-	-	Electronic Instant Start
EPS	EPS	(Blank)	EPS	-	(Blank)	(Blank)	(Blank)	(Blank)	(Blank)	(Blank)	Electronic Program Start

Consult Factory for ADVANCE or LUTRON dimming ballast options.