



#### APPLICATION:

General illumination for health care facilities, educational institutions, airports, commercial offices, retail and many other applications.

#### PRODUCT FEATURES:

- Twilite Series proprietary "light lock system" prevents light leakage at both ends of lamp shield
- Steel side reflectors intersect with housing to ensure seamless appearance
- Lamp shield pivots down for easy installation of lamps
- Ballast can be accessed from below the ceiling
- Post-painted soft white powder coat finish maximizes distribution and efficiency while providing visual comfort
- Lamp shield is 60% perforated white steel mesh, backed with high-transmission white acrylic diffuser for optimum light efficiency, maximum glare control and lamp image prevention
- All sides and corners are turned in and hemmed, removing sharp edges for safe handling and installation
- Four corner tie points are standard for safety wire support when required
- Built-in earthquake clips standard
- Same-day shipping on most options (Consult factory)
- Supplied standard with Philips Advance, GE or Universal ballast
- Wide variety of dimming and daylight harvesting options available
- Consult factory for continuous row mounting
- CEE qualified ballast comes standard on most fixture options (Consult factory for details)
- NEC required ballast disconnect is standard

#### LISTING

UL/C-UL listed to US and Canadian standards

#### WARRANTY

Guaranteed for one year against mechanical defects

### Ordering Information > Example: 24-OD-3-32-T8-ADV-10-MVOLT

<b>24</b>	<b>OD</b>								
<b>FIXTURE SIZE</b> 24-2' X 4'	<b>TRIM TYPE</b> (Blank)-Grid (Consult factory for Slot T mounting option)		<b>VOLTAGE<sup>2</sup></b> (Blank)- MVOLT (120/277) 120 277 347		<b># OF BALLAST</b> (Blank) - 1 Ballast 2 - 2 Ballasts		<b>BALLAST FACTOR</b> (Blank)- Normal BF HBF- High BF LBF- Low BF		<b>LAMP INSTALLED</b> (Blank)- No lamp L30K- 3000K L35K- 3500K L41K- 4100K L50K- 5000K
<b>SERIES</b> OD-Oracle Direct/ Indirect	<b># OF LAMPS/LAMP TYPE</b>		<b>*MASTER/SATELLITE</b> MAS1-Master fixture w/ 1 ballast & 11 ft. flex MAS2-Master fixture w/ 2 ballast & 11 ft. flex SAT-Satellite fixture w/o ballast <i>*must be ordered separately</i> EX: 24-OD-2-32-T8-MAS2 and 24-OD-2-32-T8-SAT <i>*Available only with 2 or 3 lamps T8 only. Dimming option is not available when ordering Master/Satellite.</i>						
	1-32-T8 (1 lamp/32W/T8) 2-32-T8 (2 lamps/32W/T8) 3-32-T8 (3 lamps/32W/T8)		1-28-T5 (1 lamp/28W/T5) 2-28-T5 (2 lamps/28W/T5) 3-28-T5 (3 lamps/28W/T5) 1-54-T5HO (1 lamp/54W/T5HO) 2-54-T5HO (2 lamps/54W/T5HO)						
	(For other lamp type, please consult factory)								
<b>BALLAST CONFIGURATION &amp; CODE</b>									
32W/T8	28W/T5	54W/T5HO	DESCRIPTION						
(Blank)	-	-	Electronic Instant Start						
EPS	(Blank) <sup>1</sup>	(Blank)	Electronic Program Start						
ADV-7	-	ADV-7 <sup>1</sup>	Advance Mark-7 <sup>2</sup>						
ADV-10	-	ADV-10 <sup>1</sup>	Advance Mark-10 <sup>2</sup>						
-	ADV-OPT	-	Advance Optanium <sup>2</sup>						
ADV-ESS	-	-	Advance Essential <sup>2</sup>						
ADV-ROVR	-	ADV-ROVR	Advance Rover <sup>2</sup>						
LUT-EHD	LUT-EHD <sup>1</sup>	LUT-EHD <sup>1</sup>	Lutron Ecosystem H-Series <sup>2</sup>						
LUT-2W <sup>1</sup>	-	-	Lutron Tu-Wire <sup>2</sup>						
LUT-EC5	LUT-EC5 <sup>1</sup>	-	Lutron Ecosystem <sup>2</sup>						
LUT-EC3	LUT-EC3 <sup>1</sup>	LUT-EC3 <sup>1</sup>	Lutron Eco-10 <sup>2</sup>						
LUT-TVE <sup>1</sup>	-	-	Lutron Tve <sup>2</sup>						
LUT-H3D	LUT-H3D <sup>1</sup>	LUT-H3D	Lutron Hi-Lume 3D <sup>2</sup>						
-	-	LUT-ECO <sup>1</sup>	Lutron Ecosystem (347V Only) <sup>2</sup>						
<sup>1</sup> - Requires 2 Ballasts for 3 lamps <sup>2</sup> - Voltage must be specified for dimming ballast.									
<b>EMERGENCY BATTERY PACK OPTIONS (L. = LUMENS)</b>									
ORDER CODE		DESCRIPTION							
EMG-T8-BX-450		Up to 450 L. for T8 or BX							
EMG-T8-BX-600		Up to 600 L. for T8 or BX							
EMG-T8-BX-700		Up to 700 L. for T8 or BX							
EMG-T8-BX-1400		Up to 1400 L. for T8 or BX							
EMG-T5-520		Up to 520 L. for T5							
EMG-T5-T5HO-700		Up to 700 L. for T5 or T5HO							
EMG-T5-T5HO-1300		Up to 1300 L. for T5 or T5HO							
EMG-T8-BX-T5-T5HO-3200		Up to 3200 L. for T8, BX, T5 or T5HO							
EMG-SD-T8-BX-T5-T5HO-1400		Self-Diagnostic 1400 L. for T8, BX, T5 or T5HO							
EMG-ICE-T8-BX-T5-T5HO-1400		ICE Pack 1400 L. for T8, BX, T5 or T5HO							
GTD		Generator Transfer Device							
MANY OTHER BODINE AND IOTA EMERGENCY PACKS ARE AVAILABLE. PLEASE CONSULT FACTORY. VISIT WWW.BODINE.COM OR WWW.IOTAENGINEERING.COM FOR MORE DETAILS.									
<b>OTHER OPTIONS</b>									
24FK		- Flange Kit for 2' X 4' Fixture				SBF		- Internal Slow-Blow Fuse	
C3		- 6' 3-wire Flex Cable (Single Circuit)				RIS		- Radio Interference Suppressor	
C4		- 6' 4-wire Flex Cable (Double Circuit)				DCR		- Dust Cover	
FBF		- Internal Fast Blow Fuse				USA		- Made in America Compliance	