



T8/T5 - 2' X 4' FLUORESCENT RECESSED VOLUMETRIC (CENTER MOUNT WITH LOUVER)



APPLICATION:

Ideal for any application which requires high-efficiency lighting with minimum energy consumption such as educational institutions, office spaces, health care facilities, office complexes and retail stores.

EFFICIENT SOLUTION:

High reflectance optical engine delivers main beam focus through the revolutionary flat High Transmission (HT) acrylic diffusing panel with low brightness glow. Center blade louvers control light and distribute light to task. With 95% transmission and 89% haze, the result is extraordinary control and efficiency.

OPTICAL SYSTEM: A+ Rated high-gloss white powder coat paint provides maximum distribution and visual comfort.

PRODUCT FEATURES:

- Dawn Series proprietary "light lock system" prevents light leakage at both ends of lamp shields
- Door frame hinges for easy installation of lamps and hassle-free maintenance
- Ballast can be accessed from below the ceiling
- All sides and corners are turned in and hemmed, removing sharp edges for safe handling and installation, built-in earthquake clips
- Construction of lamp shields conceals lamps and ballast access cover
- Supplied standard with Philips Advance, GE or Universal ballast
- Wide variety of dimming and daylight harvesting options available
- CEE qualified ballast comes standard on most fixture options (Consult factory for details)
- NEC required ballast disconnect is standard

LISTING

UL/C-UL listed to US and Canadian standard

WARRANTY

Guaranteed for one year against mechanical defects

Ordering Information > Example: 24-OD4V-2-32-T8-ADV-10-MVOLT

| | | | | | | | | | |
|--|---|---|---|--|--|--|---|--|--|
| 24 | OD4V | | | | | | | | |
| FIXTURE SIZE 24-2' X 4' | TRIM TYPE (Blank)-Grid (Consult factory for Slot T mounting option) | VOLTAGE (Blank)- MVOLT (120/277) 120 277 347 | | | # OF BALLAST (Blank) - 1 Ballast 2 - 2 Ballasts | BALLAST FACTOR (Blank)- Normal BF HBF- High BF LBF- Low BF | LAMP INSTALLED (Blank)- No lamp L30K- 3000K L35K- 3500K L41K- 4100K L50K- 5000K | | |
| SERIES OD4V-Oracle Dawn Direct/Indirect | # OF LAMPS/LAMP TYPE | | | *MASTER/SATELLITE | | | | | |
| | 1-32-T8 (1 lamp/32W/T8) 2-32-T8 (2 lamps/32W/T8) 3-32-T8 (3 lamps/32W/T8) | 1-28-T5 (1 lamp/28W/T5) 2-28-T5 (2 lamps/28W/T5) 3-28-T5 (3 lamps/28W/T5) | 1-54-T5HO (1 lamp/54W/T5HO) 2-54-T5HO (2 lamps/54W/T5HO) 3-54-T5HO (3 lamps/54W/T5HO) | MAS1 -Master fixture w/ 1 ballast & 11 ft. flex MAS2 -Master fixture w/ 2 ballast & 11 ft. flex SAT -Satellite fixture w/o ballast <i>*must be ordered separately</i> <i>EX: 24-OD4V-2-32-T8-MAS2 and 24-OD4V-2-32-T8-SAT</i> | | | | | |
| | (For other lamp type, please consult factory) | | | <i>*Available only with 2 or 3 lamps T8 only. Dimming option is not available when ordering Master/Satellite.</i> | | | | | |

| BALLAST CONFIGURATION & CODE | | | |
|------------------------------|---------|----------|---|
| 32W/T8 | 28W/T5 | 54W/T5HO | DESCRIPTION |
| (Blank) | - | - | Electronic Instant Start |
| EPS | (Blank) | (Blank) | Electronic Program Start |
| ADV-7 | - | ADV-7 | Advance Mark-7 ¹ |
| ADV-10 | - | ADV-10 | Advance Mark-10 ¹ |
| - | ADV-OPT | - | Advance Optanium ¹ |
| ADV-ESS | - | - | Advance Essential ¹ |
| ADV-ROVR | - | ADV-ROVR | Advance Rover ¹ |
| LUT-EHD | LUT-EHD | LUT-EHD | Lutron Ecosystem H-Series ¹ |
| LUT-2W | - | - | Lutron Tu-Wire ¹ |
| LUT-EC5 | LUT-EC5 | - | Lutron Ecosystem ¹ |
| LUT-EC3 | LUT-EC3 | LUT-EC3 | Lutron Eco-10 ¹ |
| LUT-TVE | - | - | Lutron Tve ¹ |
| LUT-H3D | LUT-H3D | LUT-H3D | Lutron Hi-Lume 3D ¹ |
| - | - | LUT-ECD | Lutron Ecosystem (347V Only) ¹ |

¹ - Voltage must be specified for dimming ballast.

EMERGENCY BATTERY PACK OPTIONS (L. = LUMENS)

| ORDER CODE | DESCRIPTION |
|----------------------------|--|
| EMG-T8-BX-450 | Up to 450 L. for T8 or BX |
| EMG-T8-BX-600 | Up to 600 L. for T8 or BX |
| EMG-T8-BX-700 | Up to 700 L. for T8 or BX |
| EMG-T8-BX-1400 | Up to 1400 L. for T8 or BX |
| EMG-T5-520 | Up to 520 L. for T5 |
| EMG-T5-T5HO-700 | Up to 700 L. for T5 or T5HO |
| EMG-T5-T5HO-1300 | Up to 1300 L. for T5 or T5HO |
| EMG-T8-BX-T5-T5HO-3200 | Up to 3200 L. for T8, BX, T5 or T5HO |
| EMG-SD-T8-BX-T5-T5HO-1400 | Self-Diagnostic 1400 L. for T8, BX, T5 or T5HO |
| EMG-ICE-T8-BX-T5-T5HO-1400 | ICE Pack 1400 L. for T8, BX, T5 or T5HO |
| GTD | Generator Transfer Device |

MANY OTHER BODINE AND IOTA EMERGENCY PACKS ARE AVAILABLE. PLEASE CONSULT FACTORY. VISIT WWW.BODINE.COM OR WWW.IOTAENGINEERING.COM FOR MORE DETAILS.

OTHER OPTIONS

| | | | |
|------|---|-----|---------------------------------|
| 24FK | - Flange Kit for 2' X 4' Fixture | SBF | - Internal Slow-Blow Fuse |
| C3 | - 6' 3-wire Flex Cable (Single Circuit) | RIS | - Radio Interference Suppressor |
| C4 | - 6' 4-wire Flex Cable (Double Circuit) | USA | - Made in America Compliance |
| FBF | - Internal Fast Blow Fuse | | |