



**APPLICATION:**

- Bathrooms
- Stairwells
- Residential
- Commercial/hospitality

**PRODUCT FEATURES:**

- Wall or ceiling mount
- Supplied with smooth white acrylic diffuser
- Diffuser easily removed via locking nut at both ends of fixture
- Standard multi-volt ballast
- Chrome end caps
- CEE qualified ballast comes standard on most fixture options (Consult factory for details)

**LISTING**

UL/C-UL listed to US and Canadian standard

**WARRANTY**

Guaranteed for one year against mechanical defects



T5  
OVLD

Ordering Information > Example: 2-OVLD-2-14-T5-MVOLT-WH

<b>2</b>	<b>OVLD</b>							
<b>FIXTURE SIZE</b> 2 - 2'	<b>SERIES</b> OVLD-Oracle Fluorescent Vanity Light Mounting	<b>WATTAGE</b> 2' FIXTURE 2-14-T5 (2 lamps/14W/T5)	<b>VOLTAGE<sup>1</sup></b> (Blank)- MVOLT (120/277) 120 277 347	<b># OF BALLAST</b> (Blank)- 1 Ballast 2- 2 Ballasts	<b>BALLAST FACTOR</b> (Blank)- Normal BF	<b>FINISH</b> WH- White SN- Satin Nickel CL- Chrome		
<b>BALLAST CONFIGURATION &amp; CODE</b>			<b>WIRING OPTIONS</b>			<b>OTHER OPTIONS</b>		
14W/T5		DESCRIPTION	FBF		- Internal Fast Blow Fuse	RS		- Rocker Switch
-		Electronic Instant Start	SBF		- Internal Slow-Blow Fuse	PCS		- Pull Chain
(Blank)		Electronic Program Start	RIS		- Radio Interference Suppressor	USA		- Made in America Compliance
Consult Factory for ADVANCE or LUTRON dimming ballast options.								

Fluorescent Surface Mount Vanity