



APPLICATION: Ambient lighting for glare-free, smooth illumination. Ideal for institutional, commercial and retail application.

PRODUCT FEATURES:

- Standard length 2,4', and 8
- Rigid aluminum extrusion made out of T6063-T5 aluminum, and die-cast aluminum end caps
- Optical system offers high efficiency LED light that passes through a smooth acrylic lens for optimal distribution patterns, thus creating a glare-free and even distribution for any application.
- Life tested to 50,000 hours of operation to L70
- Tested to LM-79 and LM-80 standards
- Full ability to tandem mount for continuous run application complete with easy quick connects

PERFORMANCE: The light engines found in the SLEEK-R-LED are rated at 85+ CRI. Rated and tested to LM-79 and LM-80 standards. The LEDs are also binned to a 3-step MacAdam ellipse to achieve consistent color from fixture to fixture.

OPTICS - Fabricated of 20 gauge aluminum. Post painted finish with 95% reflective premium paint.

DIFFUSER - Smooth white frosted acrylic lens for glare-free light and even distribution. Precision cut, snap in design.

FABRICATION - Available in 100% downlight configuration. Rigid design made with extruded aluminum ensures longevity and endurance.

FINISH - Aluminum electrostatic painted in White, Silver or custom colors.

MOUNTING - Comes standard with adjustable cable suspension system providing fast installation for a variety of interior heights, including sloped ceilings. Can be used for single or continuous row mounting in suspended or ceiling mount applications.

ENDCAPS - Rigid aluminum extrusion made out of T6063-T5 aluminum, and rounded die-cast end caps.

STANDARD LENGTHS - All luminaires are supplied in nominal lengths to ensure even illumination. Runs and configurations are available in app. 2', 4', 6' and 8' increments.

CRM INSTALLATION - For continuous row mounting, the first fixture in the row will always be the power supply feed. After plugging in the male and female harnesses, which are supplied with each fixture, they will easily slide together, then secured with two screws from opposite directions in the connecting brackets. This allows for fixtures to be continuously connected by only removing the lenses. There is no need to remove any other parts in the fixture to install the continuous run.

ELECTRICAL - Powered by high-quality constant-current power LED drivers which are rated for 50 to 60Hz at 120V-277V input, producing less than 20% THD, and a power

factor of .90 to 1.00. Male and Female 18-gauge 6-wire plug connectors are included with every fixture to allow for simple hassle-free continuous wiring. Each fixture must be installed male to female.

DIMMING AND TUNING CONTROL SYSTEMS PROVIDED BY ELITE LIGHTING. ELITE-CONNECT RGB+WHITE Hard Wired DMX 512 Wall-Mount Controller to controls RGB Colors, CCT Tuning and Intensity. Hard Wired Wall-Mount Controller easily control RGB colors, CCT Tuning and Intensity with Touchscreen pad, controlling one zone and 3 different scenes, provided by Elite Lighting.

RGB + TUNABLE WHITE: Smart Hue by Oracle is a Color Tuning across a tuning range of either 8000-1650 (RGBW-LTX-80K-16K) using Lumenix components or 6000-1650 (RGBW--60K-16K) using Elite components. Light can be dimmed from 100-1% while maintaining constant CCT. Gradients of saturated colors from 1-100% can be added to color points within the tuning range. Smart Hue can change a spaces' atmosphere by manipulating the color temperature of the room. For instance, the temperature is warm at sunrise, cool at noon high, and warm again by sunset. With Smart Hue, you can mimic the daylight patterns in indoor space with electric light or gradients of saturated colors from 1-100% that can be added to color points within the tuning range. This creates a more contrasting environment, which is perceived to be more exciting to the brain and helps people to adjust their moods accordingly.

DIMMING INFORMATION FOR Oracle SMART HUE: ELITE PLATFORM:

DMX-512 (DMX 512 channel driver options/ Consult Factory for Details)

QUALITY CONTROL - Every fixture is rigorously tested by our QC Department before shipping.

OUR WORD - Our LED system is Life tested to ensure light output of L70 up to 110,000 hrs and L85 up to 65,000 hrs and carries a five-year carefree warranty for parts and components. (Labor not included)

Ordering Information: Example: 2-SLEEK-R-LED-RGBW-60K-16K-1500L-DMX-512-MVOLT-85

	SLEEK-S-LED							
SINGLE RUN	SERIES	TECH	LUMENS	DIMMING	VOLTAGE	CRI	EMERGENCY	MOUNTING
2 - 2' 4 - 4' 8 - 8'	SLEEK-R-LED-Oracle Pendant LED Linear	RGBW-60K-16K	2' 1500L (1500 LUMENS) 4' 3000L (3000 LUMENS) 8' 6000L (6000 LUMENS)	DMX-512	347* * Consult factory for details	85	O-EMG-LED	CRM - Continuous Row Mounting