



APPLICATION:

For general lighting in parking lots, garages, stairwells, loading docks, walkways, apartment buildings, recreation facilities, underpasses, and tunnels. Highly recommended for public spaces where vandalism and abuse are a concern.

CONSTRUCTION

Die-cast aluminum housing with 1/2" coin plugs with O-rings for conduit and photocell. Back reflector is made of white powder coat steel. The one-piece silicone gasket effectively limits outside contaminants by sealing off the optical chamber. HID & HPS fixtures have porcelain 4KV pulse-rated medium-base socket with nickel-plated screw shell sockets. CFL fixtures have 4-pin plug-in base and standard ballast of minimum starting temperature of 0°F/-18°C. Extreme temperature ballast (XT) with -20°F/-30°C is available.

INSTALLATION

Fixture easily mounts directly over a 4" recessed outlet box or use 1/2" surface conduit.

LISTINGS

UL/C-UL for wet location.

LAMP

Included except for CFL option.

FINISH

Dark bronze corrosion-resistant polyester powder finish is standard.

All specifications are subject to change without notice

LENS

High-impact UV-stabilized polycarbonate diffuser held in place with high-impact screws.

Ordering Information > Example: OPG-201-MH-175-120-PC120-BZ

OPG-201					
SERIES	WATTAGE	VOLTAGE	OPTIONS	COLOR	ACCESSORIES
OPG-201 - Oracle Conical Vandal Resistant	HPS, MH HPS-70 - (70W High Pressure Sodium) HPS-100 - (100W High Pressure Sodium) HPS-150 - (150W High Pressure Sodium) MH-70 - (70W Metal Halide) MH-100 - (100W Metal Halide) MH-150 - (150W Metal Halide) MH-175 - (175W Metal Halide)	HPS, MH^{1,4} - 120 - MVOLT (120/208/240/277) - 347 ⁵ - 480 ⁵	PC120 - Photo control (120V only) PC277 - Photo control (277V only) SF - Single fuse DF - Double fuse O-EMG-750 - 750 lum. Emg. (CFL only) XT - 20°F/-30°C Min. Temp. Bal. (CFL only)	BZ - Bronze WH - White	OPG-201-RL - Replacement lens kit
	CFL CFL-1X26 - (1X26W Compact Fluorescent) CFL-1X32 - (1X32W Compact Fluorescent) CFL-1X42 - (1X42W Compact Fluorescent) CFL-2X26 - (2X26W Compact Fluorescent) CFL-2X32 - (2X32W Compact Fluorescent) CFL-2X42 - (2X42W Compact Fluorescent)	CFL^{2,3,4} - 120 - MVOLT(120/277) - 208 - 240 - 347			
	INDUCTION IND-40-50K⁶ - (40W Induction)	INDUCTION⁶ - MVOLT(120/277)			

NOTES:

1. Pulse-Start standard on all fixtures above 175W.
2. Lamps are not included for CFL.
3. Please consult factory for dimming options.
- 4 (Consult factory) for other wattages and options.
5. 347 & 480 Volt not available on 50 & 70W fixture.
6. Induction fixtures shipped with 5000k lamp standard please contact factory for other color options.