



**APPLICATION:**

For general lighting in parking lots, garages, stairwells, loading docks, walkways, apartment buildings, recreation facilities, underpasses, and tunnels. Highly recommended for public spaces where vandalism and abuse are a concern.

**CONSTRUCTION**

Die-cast aluminum housing with 1/2" coin plugs with O-rings for conduit and photocell. Back reflector is made of white powder coat steel. The one-piece silicone gasket effectively limits outside contaminants by sealing off the optical chamber. HID & HPS fixtures have porcelain 4KV pulse-rated medium-base socket with nickel-plated screw shell sockets. CFL fixtures have 4-pin plug-in base and standard ballast of minimum starting temperature of 0°F/-18°C. Extreme temperature ballast (XT) with -20°F/-30°C is available.

**FINISH**

Dark bronze corrosion-resistant polyester powder finish is standard.

**LENS**

High-impact UV-stabilized polycarbonate diffuser held in place with high-impact screws.

**INSTALLATION**

Fixture easily mounts directly over a 4" recessed outlet box or use 1/2" surface conduit.

**LISTINGS**

UL/C-UL for wet location.

**LAMP**

Included except for CFL option.

**All specifications are subject to change without notice**

**Ordering Information > Example: OPG-202-MH-100-120-PC120-BZ**

<b>OPG-202</b>					
<b>SERIES</b>	<b>WATTAGE</b>	<b>VOLTAGE</b>	<b>OPTIONS</b>	<b>COLOR</b>	<b>ACCESSORIES</b>
<b>OPG-202</b> - Oracle Medium Round Vandal Resistant	<b>HPS, MH</b> <b>HPS-50</b> - (50W High Pressure Sodium) <b>HPS-70</b> - (70W High Pressure Sodium) <b>HPS-100</b> - (100W High Pressure Sodium) <b>MH-50</b> - (50W Metal Halide) <b>MH-70</b> - (70W Metal Halide) <b>MH-100</b> - (100W Metal Halide)	<b>HPS, MH<sup>1,4</sup></b> - 120 - MVOLT (120/208/240/277) - 347 <sup>5</sup> - 480 <sup>5</sup>	<b>PC120</b> - Photo control (120V only) <b>PC277</b> - Photo control (277V only) <b>SF</b> - Single fuse <b>DF</b> - Double fuse <b>O-EMG-750</b> - 750 lum. Emg. (CFL only) <b>XT</b> - 20°F/-30°C Min. Temp. Bal. (CFL only)	<b>BZ</b> - Bronze	<b>OPG-202-RL</b> - Replacement lens kit
	<b>CFL</b> <b>CFL-1X26</b> - (1X26W Compact Fluorescent) <b>CFL-1X32</b> - (1X32W Compact Fluorescent) <b>CFL-1X42</b> - (1X42W Compact Fluorescent)	<b>CFL<sup>2,3,4</sup></b> - 120 - MVOLT(120/277) - 208 - 240 - 347			

**NOTES:**

1. Pulse-Start standard on all fixtures above 175W.
2. Lamps are not included for CFL.
3. Please consult factory for dimming options.
4. (Consult factory) for other wattages and options.
5. 347 & 480 Volt not available on 50 & 70W fixture.