



**APPLICATION:**

For general lighting in parking lots, garages, stairwells, loading docks, walkways, apartment buildings, recreation facilities, underpasses, and tunnels. Highly recommended for public spaces where vandalism and abuse are a concern.

**CONSTRUCTION**

Die-cast aluminum housing with 1/2" coin plugs with O-rings for conduit and photocell. Back reflector is made of white powder coat steel. The one-piece silicone gasket effectively limits outside contaminants by sealing off the optical chamber. HID & HPS fixtures have porcelain 4KV pulse-rated medium-base socket with nickel-plated screw shell sockets. CFL fixtures have 4-pin plug-in base and standard ballast of minimum starting temperature of 0°F/-18°C. Extreme temperature ballast (XT) with -20°F/-30°C is available.

**FINISH**

Dark bronze corrosion-resistant polyester powder finish is standard.

**LENS**

High-impact UV-stabilized polycarbonate diffuser held in place with high-impact screws.

**INSTALLATION**

Fixture easily mounts directly over a 4" recessed outlet box or use 1/2" surface conduit.

**LISTINGS**

UL/C-UL for wet location.

**LAMP**

Included except for CFL option.

**All specifications are subject to change without notice**

**Ordering Information > Example: OPG-302-MH-150-120-PC120-BZ**

|   |  |   |  |              |                                   |
|---|--|---|--|--------------|-----------------------------------|
| <b>OPG-302</b>                                      |  |   |  |              |                                   |
| <b>SERIES</b>                                       | <b>WATTAGE</b>   | <b>VOLTAGE</b>  | <b>OPTIONS</b>   | <b>COLOR</b> | <b>ACCESSORIES</b>                |
| OPG-302 - Oracle<br>Large Round<br>Vandal Resistant | <b>HPS, MH</b><br>HPS-100 - (100W High Pressure Sodium)<br>HPS-150 - (150W High Pressure Sodium)<br>MH-100 - (100W Metal Halide)<br>MH-150 - (150W Metal Halide)<br>MH-175 - (175W Metal Halide)   | HPS, MH <sup>1,4</sup><br>- 120<br>- MVOLT<br>(120/208/240/277)<br>- 347 <sup>5</sup><br>- 480 <sup>5</sup> | PC120 - Photo control (120V only)<br>PC277 - Photo control (277V only)<br>SF - Single fuse<br>DF - Double fuse<br>O-EMG-750 - 750 lum. Emg. (CFL only)<br>XT - 20°F/-30°C Min. Temp. Bal. (CFL only) | BZ - Bronze  | OPG-302-RL - Replacement lens kit |
|   | <b>CFL</b><br>CFL-1X26 - (1X26W Compact Fluorescent)<br>CFL-1X32 - (1X32W Compact Fluorescent)<br>CFL-1X42 - (1X42W Compact Fluorescent)<br>CFL-2X26 - (2X26W Compact Fluorescent)<br>CFL-2X32 - (2X32W Compact Fluorescent)<br>CFL-2X42 - (2X42W Compact Fluorescent) | <b>CFL<sup>2,3,4</sup></b><br>- 120<br>- MVOLT(120/277)<br>- 208<br>- 240<br>- 347                          |  |              |                                   |
|   | <b>INDUCTION</b><br>IND-40-50K <sup>6</sup> - (40W Induction)<br>IND-80-50K <sup>6</sup> - (80W Induction)   | <b>INDUCTION<sup>6</sup></b><br>- MVOLT(120/277)  |  |              |                                   |

**NOTES:**

1. Pulse-Start standard on all fixtures above 175W.
2. Lamps are not included for CFL.
3. Please consult factory for dimming options.
- 4 (Consult factory) for other wattages and options.
5. 347 & 480 Volt not available on 50 & 70W fixture.
6. Induction fixtures shipped with 5000k lamp standard please contact factory for other color options.