



**APPLICATION:**

For general lighting in parking lots, garages, stairwells, loading docks, walkways, apartment buildings, recreation facilities, underpasses, and tunnels. Highly recommended for public spaces where vandalism and abuse are a concern.

**CONSTRUCTION**

Die-cast aluminum housing with 1/2" coin plugs with O-rings for conduit and photocell. Back reflector is made of white powder coat steel. The one-piece silicone gasket effectively limits outside contaminants by sealing off the optical chamber. HID & HPS fixtures have porcelain 4KV pulse-rated medium-base socket with nickel-plated screw shell sockets. CFL fixtures have 4-pin plug-in base and standard ballast of minimum starting temperature of 0°F/-18°C. Extreme temperature ballast (XT) with -20°F/-30°C is available.

**FINISH**

Dark bronze corrosion-resistant polyester powder finish is standard.

**LENS**

High-impact UV-stabilized polycarbonate diffuser held in place with high-impact screws.

**INSTALLATION**

Fixture easily mounts directly over a 4" recessed outlet box or use 1/2" surface conduit.

**LISTINGS**

UL/C-UL for wet location.

**LAMP**

Included except for CFL option.

**All specifications are subject to change without notice**

**Ordering Information > Example: OVR-201-MH-70-120-PC120-BZ**

<b>OVR-201</b>					
<b>SERIES</b>	<b>WATTAGE</b>	<b>VOLTAGE</b>	<b>OPTIONS</b>	<b>COLOR</b>	
OVR-201 - Oracle Medium Square Vandal Resistant	<b>HPS, MH</b> HPS-50 - (50W High Pressure Sodium) HPS-70 - (70W High Pressure Sodium) MH-50 - (50W Metal Halide) MH-70 - (70W Metal Halide)	<b>HPS, MH<sup>1,4</sup></b> - 120 - MVOLT (120/208/240/277) - 347 <sup>5</sup> - 480 <sup>5</sup>	PC120 - Photo control (120V only) PC277 - Photo control (277V only) SF - Single fuse DF - Double fuse O-EMG-750 - 750 lum. Emg. (CFL only) XT - 20°F/-30°C Min. Temp. Bal. (CFL only)	BZ - Bronze WH - White	
	<b>CFL</b>	<b>CFL<sup>2,3,4</sup></b>			<b>ACCESSORIES</b>
	CFL-1X26 - (1X26W Compact Fluorescent) CFL-1X32 - (1X32W Compact Fluorescent) CFL-1X42 - (1X42W Compact Fluorescent) CFL-2X26 - (2X26W Compact Fluorescent)	- 120 - MVOLT(120/277) - 208 - 240 - 347			OVR-201-RL - Replacement lens kit

**NOTES:**

1. Pulse-Start standard on all fixtures above 175W.
2. Lamps are not included for CFL.
3. Please consult factory for dimming options.
- 4 (Consult factory) for other wattages and options.
5. 347 & 480 Volt not available on 50 & 70W fixture.