LEO




ST801-AL **Angle Louvered**



ST802-AL **Diffused Glass Lens**





APPLICATION: For concrete use only

BODY: Galvanized steel

FACE PLATE: High-grade die-cast aluminum

Supplied standard with two 3/4" knockouts located on sides. **GASKET:** Single piece molded silicon for wet location

LENS: Frosted tempered glass FINISH: Bronze thermoset powder coat

EXTERNAL LOUVER: Anodized 45" cut-off louver

REFLECTOR: High performance aluminum reflector assembly for superb light output.

INSTALLATION: Two 1/2" NPS wiring holes


Feed through listed

BALLAST: Thermally protected, current controlled ballast, will produce full light output,

increase lamp LIFE with no noise or flicker.

UL/ cUL for wet locations.

Ordering Example: ST8BX-LED-WW-12V-ST801-WH





ST7BX LED EXTERIOR STEP LIGHTS SERIES



ST701-BR **Angle Louvered**




ST702-BR **Diffused Glass Lens**



ST703-BR **Cover with Lens**





APPLICATION: For concrete use only

BODY: High grade die-cast aluminum with 0.3% Copper to prevent corrosion in concrete applications.

Supplied standard with three 3/4" NPS holes located on top, side & back.

FACE PLATE: High-grade die-cast aluminum **GASKET:** Single piece molded silicon for wet location

LENS: Frosted tempered glass

EXTERNAL LOUVER: Anodized 45" cut-off louver

REFLECTOR: High performance aluminum reflector assembly for superb light output.


INSTALLATION: Two 1/2" NPS wiring holes Feed through listed

BALLAST: Thermally protected, current controlled ballast, will produce full light output, increase lamp life with no noise or flicker.

LISTING:

UL/ cUL for wet locations.

Ordering Example: ST7BX-LED-WW-12V-ST701-WH



*MUST BE USED WITH REMOTE DRIVER

