

#### PROJECT INFORMATION

Project Name	Туре
Catalog #	Date

# **HIGH BAY RECESSED**



#### **APPLICATIONS**

- · Industrial & Manufacturing
- Sports & Fitness
- Retail Spaces
- · Commercial Spaces
- Show Rooms
- · Recessed Grids

#### **APPROVALS**

- Complies with UL 1598 and CSA C22.2
- Suitable for damp locations
- BAA Compliant



## **FEATURES**

- Lumen packages ranging from 10000L to 19500I
- A high performing luminaire designed to light large areas in commercial and industrial applications with recessed grids.
- Thermal heat management engineered for extended life.
- Access to driver from room side.
- Earthquake clips standard.

## **CONTROLS**

· Consult factory for control options.

## **CONSTRUCTION**

- Aluminum post-painted powder coat white.
- Flat lens within lens frame available in multiple options of material and texture.

## **ELECTRICAL**

- Voltage: 120-277V AC input
- Driver: Class 2, constant current, calibrated to lumen packages (0-10V dimming standard)

## **MOUNTING**

• Designed for common 15/16" ceiling grid and hard ceiling flange kit accessory available.

## WARRANTY

• Backed by XtraLight's limited 5-year warranty.

## **ORDER LOGIC**

## SAMPLE CATALOG NUMBER: LHF24-15000L-50K-DIM-PFA


HR						
	SIZE	MODEL	ССТ	DRIVER	LENS/OPTICS	OPTIONS
	<b>22</b> 2X2 <b>24</b> 2X4	10000L 15000L 19500L	<b>30K</b> 3000K <b>35K</b> 3500K <b>40K</b> 4000K <b>50K</b> 5000K	<b>DIM</b> Dim 0-10V, 120-277V	PFA Prismatic Frosted Acrylic SFP Smooth Frosted Polycarbonate SCP Smooth Clear Polycarbonate	EM Emergency Battery Back-up WG Wire Guard




# **HIGH BAY RECESSED**

## **LHR**

## **ISO LINES**







#### **PHOTOMETRIC DATA**

SIZE	MODEL	ССТ	LENS / OPTICS	LUMENS	WATTAGE	EFFICACY
2X2	19500L	5000K	SCP	21773	192.4	113.2

## **DIMENSIONAL DATA**

#### **STANDARD SIZES**





## **ACCESSORIES** (SOLD SEPARATELY)

## **FLANGE KIT SIZE**

MS2807 2X2 Troffer MS2806 2X4 Troffer

## **DESCRIPTION**

- Flange Kit
- Act as T-Bar frames to support the luminaire in wood, drywall or plaster ceilings
- Mimics the appearance of T-Bars. All kits include (2) side flanges, (2) end flanges and (8) short 8/32 hex screws



- Consult factory for further data and lumen multipliers.
  Dimensional data shows the end and top views for all standard sizes.
  Consult factory for product weights.

