











APPLICATIONS	Direct/Indirect luminaire for exterior applications: flanking doors, lobby entrances or between windows. Materials specifically for use in corrosive and harsh environments.
SIZE	• 12" L x 12" W x 4" D, 8 lbs
MOUNTING	 J-Box 3.0 or 4.0 at center or end of fixture Steel mounting system with mounting plate and cover with rubber gaskets between the junction box and mounting plate Can be mounted vertically or horizontally
SPECIFICATIONS	 IP66 Rated May be Power Washed at High Pressure (100kPa at distance of 3m) 120-277V input Title 24 Compliant ADA Compliant 100,000+ hours rated life time 10 Year Limited Warranty (excludes shade)
LAMPING	 High efficiency, fully integrated propietary LED module 80 CRI minimum (85 CRI typical) CCT Options: 3000K, 3500K TEX-SQ-12: 24W. 792 lumens delivered TEX-SQ-18: 36W. 1188 lumens delivered 0-10V Dimming (100-10%)
CONSTRUCTION	Fixture shell (shade): Heavy gauge aluminum with industrial powder coat finish and high impact acrylic


SPECIFICATIONS SUBJECT TO CHANGE

TEX Squared


ARCHITECTURAL SCALE, WET-LISTED EXTERIOR WALL SCONCE




DIMENSIONS




PHOTOMETRIC RESULTS





METAL POWDER COAT FINISH OPTIONS













ESN - Enviro Satin Nickel

Bronze

WHT - White

BLK - Black

GR - Graphite

DB - Dark Bronze



ORDER CODE:

TEX-SQUARED

MODEL

SIZE

18 18.5"L x 18.5"W x 4"D

12 12"L x 12"W x 4"D

POWDER COAT METAL FINISH

ESN Enviro Satin Nickel
EOB Enviro Oil-Rubbed Bronze

GR Graphite
DB Dark Bronze

WHT White
BLK Black

CCT

3000 3000K

3500 3500K