

# M800R/MCLR8W


120V-277VAC LED 8", Non-IC, Remodel Frame-in Kit  
Down Light with interchangeable Reflector Trims

Catalog		Type
Project		Date
Prepared		


## 8" LED Remodel Frame-in Kit





6-7/8"  
(174.4mm)



7-5/8"  
(193.7mm)



7-1/8"  
(181mm)



15-3/16"  
(386mm)

Ceiling Cut-out : 8"-1/8"

## DESCRIPTION

The **M800R/MCLR8W** is an 8" LED, Non-IC Remodel Frame-in kit and is available with multiple Trim styles. Designed for use in non-insulated ceilings, Insulation material must be kept a minimum of 3" from fixture. Available with a 14W, 23W, 30W or 45W, high efficacy LED engine and universal, dimmable drivers. The special optical diffuser produces high lumen transmission and even illumination. Suitable for Wet Locations.

## DESIGN FEATURES

### LED Module & Trim

- Painted, extruded aluminum heat sink designed to facilitate efficient heat dissipation for superior thermal management and reliability.
- LED engine includes LED, heat sink and lens assembly.
- Heavy gauge aluminum reflector anodized in clear haze or white paint finishes. Multiple trim styles and finishes are available.

### LED Driver

- Universal, 120~277V input, high efficacy drivers with dimming capability by ① a Triac 120V low voltage electronic dimmer switches or ② 0-10V, Triac & ELV dimmer switches.
- Drivers feature power factor >.90, THD <20% with integral thermal protection to sense over temperature or electrical issues.
- Driver mounts externally to the module to allow future replacement or upgrading if desired.
- Optional Lutron Hi-lume A-Series, LED drivers and EcoSystem 5-Series LED drivers are available. Lutron drivers provide flicker-free, smooth, continuous dimming down to 1% for Hi-lume and 5% for EcoSystem. (Contact factory for dimming system requirements)

### Remodel Clips

- 3 remodel clips secure housing into the ceiling and accommodates 1/2" and 5/8" ceiling materials.

### Junction Box

- Listed for through branch circuit wiring. (Max.8 No 12 AWG 90 branch circuit conductors: 4 in, 4 out)
- (5) 1/2" knockouts with pry-out slots and (4) knockouts with Romex cable clamps.
- Ground wire provided on J-box.

### Options

- Emergency battery back-up : Available in mounted to fixture or remote, adjacent to luminaire (consult with factory for space requirements).

### Limited Warranty


- LED Module: 5 years/50K hours
- Product/Driver: 3 years

### Listing

- cETLus Wet Location
- ENERGY STAR
- California Title 24

SPECIFICATION				
Input Voltage	120-277VAC			
Wattage (+/-5%)	14W	23W	30W	45W
Lumen (+/-5%)	960	1,760	2,280	3,340
Efficacy (LPW)	68.6	76.5	76	74.2
Beam Angle	63°	64.2°	63.3°	62.9°
CRI (Typical)	80, 90			
CCT (Color +/-5%)	2700K, 3000K, 3500K, 4000K			
Dimming	0-10V, ELV & TRIAC Optional Lutron Drivers			
LED Module	5 yr/50K hr			
Environment	Wet Location			

Triac Approved Dimmers
* Lutron: NovaT (Ntely 300 & 600) Diva (Dvelv-300P&303P)
* Leviton: Acenti: Ate06-1Lw
* Leviton Trimatron #705W (incandescent)
0-10V Approved Dimmers
* Lutron: Nova® 0-10V : NTFTV Diva® 0-10V : DVTV
* Leviton: Decora 0-10V : IP710DL
Consult tech. service or factory for additional dimmers

* Provided: Easy-quick connector case (patent pending)


# M800R/MCLR8W

120V-277VAC LED 8", Non-IC, Remodel Frame-in Kit  
Down Light with interchangeable Reflector Trims

Catalog		Type
Project		Date
Prepared		

## 8" LED Remodel Frame-in Kit

### TRIM

\* Wide beam reflector is standard. Also available narrow beam in reflector(consult with factory).



**MCLR8W-HC**  
Specular Open  
Reflector


**MCLR8W-B**  
Baffle w / Reflector

**MCLR8W-BL**  
Baffle w / Regressed  
Lens

**MCLR8W-CL**  
Reflector w /  
Regressed Lens

**MCLR8W-HCW**  
Wall Wash  
w / Reflector  
Plate

**MCLR8W-HCWL**  
Wall Wash w / Spread Lens  
Fixed for Wall or Sloped  
Ceilings 25 to 35 Degree




**MCLR8W-DLC**  
Reflector with Frosted 3.5"  
Center Hole Lens

\* All trims are rated for damp location and regressed lens trims are wet location listed.

## PHOTOMETRIC REPORT

\* Contact Factory for IES File




**Illuminance at a Distance**

Center Beam FC	Beam Width
2.0ft 163.9 fc	3.1 ft
4.0ft 41.0 fc	6.3 ft
6.0ft 18.2 fc	9.4 ft
8.0ft 10.2 fc	12.5 ft
10.0ft 6.6 fc	15.7 ft
12.0ft 4.6 fc	18.8 ft

Beam Spread: 63.3°

[MCLR8W-14-830-HC-WH]




**Illuminance at a Distance**

Center Beam FC	Beam Width
2.0ft 378.7 fc	2.5 ft
4.0ft 94.7 fc	5.0 ft
6.0ft 42.1 fc	7.5 ft
8.0ft 23.7 fc	10.0 ft
10.0ft 15.1 fc	12.5 ft
12.0ft 10.5 fc	15.0 ft

Beam Spread: 64.2°

[MCLR8W-23-830-HC-WH]




**Illuminance at a Distance**

Center Beam FC	Beam Width
2.0ft 497.7 fc	2.5 ft
4.0ft 124.4 fc	4.9 ft
6.0ft 55.3 fc	7.4 ft
8.0ft 31.1 fc	9.9 ft
10.0ft 19.9 fc	12.3 ft
12.0ft 13.8 fc	14.8 ft

Beam Spread: 63.3°

[MCLR8W-30-830-HC-WH]



**Illuminance at a Distance**

Center Beam FC	Beam Width
2.0ft 732.2 fc	2.4 ft
4.0ft 183.1 fc	4.9 ft
6.0ft 81.4 fc	7.3 ft
8.0ft 45.8 fc	9.8 ft
10.0ft 29.3 fc	12.2 ft
12.0ft 20.3 fc	14.7 ft

Beam Spread: 62.9°

[MCLR8W-45-830-HC-WH]

## Ordering Information

Model	-Watts	-CRI	Color Temp.**	Driver*	Trim	-Reflector Finish**	Baffle Finish for B & BL	Optional Metal Trim Ring Finish
<b>M800R</b> = 8", Non-IC, Remodel Frame-in Down Light Kit	-14 = 14W -23 = 23W -30 = 30W -45 = 45W	-8 = 80 -9 = 90	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	<b>T</b> = 120-277VAC, Triac: 10-100% Dimming (14, 23 & 30W only) <b>Z</b> = 120-277V, 0-10V, Triac & ELV: 1-100% Dimming <b>LTD</b> = Lutron Hi-Lume 1% Dimming <b>LSD</b> = Lutron EcoSystem 5% Dimming *- Option -EM = Emergency battery backup	<b>MCLR8W-HC</b> <b>MCLR8W-B</b> <b>MCLR8W-BL</b> <b>MCLR8W-CL</b> <b>MCLR8W-HCW</b> <b>MCLR8W-HCWL</b> <b>MCLR8W-DLC</b>	-HC = Haze Clear -WH = White Painted	-WH = White -BK = Black	-WH = White Plastic Trim Ring (Standard) -WMR = White Metal Ring -SN = Satin Nickel -CH = Chrome -SF = Polished Self-Flange (for Open or Wall Wash Reflectors ONLY)

Example : M800R-14-830-Z

MCLR8W-HC-WH

\*\* Consult factory for other Color Temperatures and Finishes