


MPL2 Series

120V and 277V
LED Pendant Lighting



Catalog		Type
Project		Date
Prepared		

LED Pendant Lighting



■ Dimension Table

Housing	MPL2	MPL25
Head D (Diameter)	2-1/8" (Ø55mm)	2-5/8" (Ø68mm)
H (Height)	5-5/8" (144mm)	6-1/2" (163.5mm)

DESCRIPTION

MPL2 & 25 Series Miniture Pendants offers superior light output and performance while maintaining a small sleek design for 2" and 2-1/2" Diecast Cylinder Shape combines premier thermal management for dependability that offer's optomized optical deliveries in different beam spreads for spot to light various applications that include counter spaces and overall general lighting.

FEATURES and FUNCTIONS

- One piece casted aluminum and heat sink designed to facilitate heat dissipation.
- Exchangeable reflector for beam angle, 25 and 40 degree.
- 120V~277V AC LED module integrated IC chip imbed on board.
- Available in stem rod or aircraft cable in varions lengths.
- 80, 90 CRI, 2700K, 3000K, 3500K, 4000K and 5000K
- Hanging aircraft cable is standard. Stem rod is available(optional).
- Triac dimming is standard.

Listing

- CSA-us Certificated
- State of California Title 24
- Energy star Approved & Listed

Warranty

- 5years of lamp life.

SPECIFICATION

HOUSING	MPL2		MPL25		
Wattage (Typ)	10W	15W	15W	20W	30W
Lumen (Typ)	600(90CRI)	907(90CRI)	975(90CRI)	1,304(90CRI)	1,950(90CRI)
Efficacy (LPW)	60 lm/W	60.5 lm/W	65 lm/W	65 lm/W	65 lm/W
Beam Angle	25° / 40°				
C R I (Typical)	80 90				
Color (+/-5%)	2700K, 3000K, 3500K, 4000K, 5000K				
Dimming	Triac & 0-10V the both(Consult with factory for approved dimmers)				

ORDERING INFORMATION

Housing	Watts	CRI	CCT	Beam Angle	Aircraft Cable Length	Finish
MPL2	10 10W	8 80	27 2700K	25 25°	12 12 Inches	WH White
	15 15W	9 90	30 3000K	40 40°	18 18 Inches	BK Black
MPL25	20 20W		35 3500K		24 24 Inches	
	30 30W		40 4000K		36 36 Inches	
			50 5000K		48 48 Inches	

*Consult with factory for custom finishes

Example: **MLP2-10-830-25-12-WH**

- - - - -