OUTDOOR Light

MCL3 Series

120V and 277V



Catalog	Туре
Project	 Date
Prepared	

3" LED Wall & Pendant Mount Cylinder light (Up/Down & Down type)

3" LED Cylinder



3-15/16" (100mm) 5**-**7/8″ 10-1/4" (150mm) (260mm) 7-1/8 6-3/16" (181mm) (157mm) 3-9/16" 2-7/16" 3-9/16" 2-7/16" (Ø90mm) (62.5mr 6-1/8" (Ø90mm) (62.5mm 6-1/8" (155mm) (155mm) [MCL3-D] [MCL3-UD]

DESCRIPTION

Wet location(IP65) rated outdoor use round cylinder type wall or pendant mount with downlight and up & down light. 13W and 27W LED AC module by customized IC, embeded circuit on board for full (5% lowest) dimming by most of Triac or 0-10V dimming switches in the market. Low heat, long life running from DOB technology can warrant more than 5 years in weather change circumstances with (-30 $C \sim +40 C$) range.

SPECIFICATION							
HOUSING							
Wattage (Typ)	13W	17W					
Lumen (Typ)	845(80CRI)	1,105(80CR I)					
Efficacy (LPW)	65 lm/W	65 lm/W					
Beam Angle	13° / 28° / 37°						
CRI (Typical)	80, 90						
Color (+/-5%)	2700K, 3000K, 3500K, 4000K, 5000K						
Dimming	Triac & 0-10V the both(Consult with factory for approved dimmers)						

FEATURES and **FUNCTIONS**

- Main body by weather proof aluminum powder coated white, black and silver finish for outdoor/indoor applications
- 13W and 17W 120V DOB modules with integrated circuit on board with customized chips (No driver needed)
- Hanging aircraft cable is standard. Also available in stem rod(For down type only)
- Also available in photocell sensor and day light harvest.
- 80, 90 CRI, 2700K, 3000K, 3500K, 4000K and 5000K
- Triac dimming is standard. Also available 0-10V dimming.

Warranty

• 5years of lamp life.

ORDERING INFORMATION

Listing

- CSA-us Certificated
- State of california Title 24
- Energy star Approved & Listed
- Wet location (IP65 Rated)

Provided

SENSOR



Housing		Watts	CRI	ССТ	Beam Angle	Housing Finish	Aircraft Cable Length	Option
MCL3-D	Down type	13 13W	8 80	27 2700K	N 13°	WH White	12 12 Inches	PCR Photocell Sensor
MCL3-UD	Up / Down Type	17 17W	9 90	30 3000K	M 28°	BK Black	18 18 Inches	
				35 3500K	W 37°	SI Silver	24 24 Inches	
MCL3	Pendant Down type			40 4000K			36 36 Inches	
				50 5000K			48 48 Inches	
						* Consult Factory for Custom Finishes	* For MCL3 only	
Example : MCL3D-13-930-M-WH-120V								

Image Arch Lighting | 10064 Dawson Canyon Road Corona, CA 92883 | (888) 220-1882 www.imagearchlighting.com © Image Arch Lighting, All Rights Reserved. This document is subject to change without notice.

