

SD-SW24/2.0

STRIP: Static White



Part of our Standard collection, SD-SW24/2.0 is an energy-efficient 24-volt, 2.0-watt/foot strip and is available in CCTs of 2400K, 2700K, 3000K, 3500K, and 4000K. Offered in dry or wet.


The SD-SW24/2.0 strip is Quick Ship eligible in CCT's of 2700K, 3000K, and 3500K and is available in full reels or custom cut lengths.

Technical Information [Calculated L70 = 70000 hours]

Tested with SD-SW24/2.0-DRY

CCT	Lumen/ft	Luminous Efficacy	CRI Ra	CRI R9	TM30 Rf	TM30 Rg
● 2400K	186	97 Lm/W	98	93	95	103
● 2700K	192	100 Lm/W	99	99	95	102
● 3000K	195	102 Lm/W	98	98	95	101
● 3500K	199	104 Lm/W	96	82	91	100
○ 4000K	225	117 Lm/W	98	98	93	101

Dimensions



Section (in)	A	B	C	D
DRY (IP20)	0.32"	0.32"	1.97"	0.06"
WET (IP67)	0.47"	0.32"	1.97"	0.21"

Part Number Builder

Model	V/Watts	Rated	CCT - Lumens/CRI	Length (in)															
SD SD: Standard Exclusive	SW24/2.0 Voltage: 24 VDC Wattage: 2.0 W/ft	^	^	2" increments															
		DRY (IP20)	<table><tr><td>24</td><td>- 2400K</td><td>186/98</td></tr><tr><td>27</td><td>- 2700K</td><td>192/99</td></tr><tr><td>30</td><td>- 3000K</td><td>195/98</td></tr><tr><td>35</td><td>- 3500K</td><td>199/96</td></tr><tr><td>40</td><td>- 4000K</td><td>225/98</td></tr></table>	24	- 2400K	186/98	27	- 2700K	192/99	30	- 3000K	195/98	35	- 3500K	199/96	40	- 4000K	225/98	48' MAX RUN LENGTH
24	- 2400K	186/98																	
27	- 2700K	192/99																	
30	- 3000K	195/98																	
35	- 3500K	199/96																	
40	- 4000K	225/98																	
		WET (IP67)	<table><tr><td>24</td><td>- 2400K</td><td>***/**</td></tr><tr><td>27</td><td>- 2700K</td><td>***/**</td></tr><tr><td>30</td><td>- 3000K</td><td>***/**</td></tr><tr><td>35</td><td>- 3500K</td><td>***/**</td></tr><tr><td>40</td><td>- 4000K</td><td>***/**</td></tr></table>	24	- 2400K	***/**	27	- 2700K	***/**	30	- 3000K	***/**	35	- 3500K	***/**	40	- 4000K	***/**	30' MAX RUN LENGTH
24	- 2400K	***/**																	
27	- 2700K	***/**																	
30	- 3000K	***/**																	
35	- 3500K	***/**																	
40	- 4000K	***/**																	

- 5 year warranty
- Field modifications must comply with Q-Tran's installation methods otherwise warranty is null & void
- All data has +/- 5% tolerance
- UL Listed
- Title 24 - JA8-2016 Strips: DRY and WET rated, 2700K and above
- Suitable for installation in the storage area of a clothes closet when assembled as a fixture at Q-Tran facility
- Available in DRY 25' & 100' reels for field installation. Contact factory


















SD-SW24/2.0

STRIP: Static White












Compatible Extrusions

	 SLIM	 WIDE	 ROND	 TORQ	 TRE3	 LALO	 TALO
DRY	✓	✓	✓	✓	✓	✓	✓
DMP							
ENC							
WET	✓ No Lens	✓		✓	✓	✓	✓

	 ARKA	 TELA	 VEVE	 FLUR	 EMBD	 LATO	 MDIN	 OPTI
DRY	✓	✓	✓	✓	✓	✓	✓	✓
DMP								
ENC								
WET	✓	✓	✓	✓	✓	✓		

Compatible Accessories

SNP-LEAD	SNP-INLINE	CLP-LEAD	CLP-INLINE	Q-mini-J	iQ-LED-24-KIT	iQ-JUMP-6-KIT	iQ-LED-67-KIT	iQ-JUMP-67-KIT
 45" .17" .61"	 45" .17" .85"	 .96" 30" .50"	 .78" 30" .50"					
DRY only 22 - 20 AWG	DRY only 22 - 20 AWG	DRY only 22 - 18 AWG	DRY only 22 - 18 AWG					