

SW24/6.0

STRIP: Static White




One step one bin static white LED strip with 526 lm/ft @ 3000K. This energy-efficient 24-volt, 6.0-watt/foot dry-rated strip features 6 diodes per 2" cut point and is available in CCTs of 2000K, 2200K, 2400K, 2700K, 3000K, 3500K, and 4000K. Choose your connection type from bare wire, barrel connectors, or not soldered. Pair with an aluminum extrusion to create a custom fixture.

Technical Information [Calculated L70 = 70000 hours]

Tested with SW24/6.0-DRY

CCT	Lumen/ft	Luminous Efficacy	CRI Ra	CRI R9	TM30 Rf	TM30 Rg
2000K	414	68 Lm/W	93	60	86	106
2200K	***	***	***	***	***	***
2400K	443	72 Lm/W	96	91	94	103
2700K	500	85 Lm/W	98	92	95	101
3000K	526	89 Lm/W	98	94	94	102
3500K	561	95 Lm/W	98	95	93	101
4000K	560	95 Lm/W	98	98	92	101

Dimensions



Part Number Builder

V/Watts	Rated	CCT - Lumens/CRI	Connector/ Wire In	Connector/ Wire Out	Wire Color	Wire Type	Illuminated Length (in)																																					
SW24/6.0 Voltage: 24 VDC Wattage: 6.0 W/ft	DRY																																											
	DRY (IP20)	<table border="1"> <tr><td>20</td><td>- 2000K</td><td>414/93</td></tr> <tr><td>22</td><td>- 2200K</td><td>***/**</td></tr> <tr><td>24</td><td>- 2400K</td><td>443/96</td></tr> <tr><td>27</td><td>- 2700K</td><td>500/98</td></tr> <tr><td>30</td><td>- 3000K</td><td>526/98</td></tr> <tr><td>35</td><td>- 3500K</td><td>561/98</td></tr> <tr><td>40</td><td>- 4000K</td><td>560/98</td></tr> </table>	20	- 2000K	414/93	22	- 2200K	***/**	24	- 2400K	443/96	27	- 2700K	500/98	30	- 3000K	526/98	35	- 3500K	561/98	40	- 4000K	560/98	<table border="1"> <tr><td>BW</td></tr> <tr><td>BRL</td></tr> <tr><td>CLS</td></tr> <tr><td>CON6</td></tr> <tr><td>CON24</td></tr> </table>	BW	BRL	CLS	CON6	CON24	<table border="1"> <tr><td>CLS</td></tr> <tr><td>BW</td></tr> <tr><td>BRL</td></tr> <tr><td>CON6</td></tr> <tr><td>CON24</td></tr> </table>	CLS	BW	BRL	CON6	CON24	<table border="1"> <tr><td>WH</td></tr> <tr><td>BK</td></tr> <tr><td>N/A</td></tr> </table>	WH	BK	N/A	<table border="1"> <tr><td>CL2</td></tr> <tr><td>CL2P</td></tr> <tr><td>N/A</td></tr> </table>	CL2	CL2P	N/A	1.96" increments Matches EXT length ordered 2"-192" OR MATCH
20	- 2000K	414/93																																										
22	- 2200K	***/**																																										
24	- 2400K	443/96																																										
27	- 2700K	500/98																																										
30	- 3000K	526/98																																										
35	- 3500K	561/98																																										
40	- 4000K	560/98																																										
BW																																												
BRL																																												
CLS																																												
CON6																																												
CON24																																												
CLS																																												
BW																																												
BRL																																												
CON6																																												
CON24																																												
WH																																												
BK																																												
N/A																																												
CL2																																												
CL2P																																												
N/A																																												

- If selecting **BRL**, select **N/A** for wire color and type
- **BW** comes in standard 24"- request custom length (Max 120") by writing it in inches next to "BW" in the order code box (ex. BW48)
- Wire orientation for **MATCH** will be dictated by extrusion Feed In/Feed Out selection
- **Connector/Wire In or Out not** needed to specify product. Standard configuration is BW for Wire In and CLS for Wire out
- **CL2** wire is standard non-plenum wire, **CL2P** wire is plenum rated

- 5 year warranty
- Field modifications must comply with Q-Tran's installation methods otherwise warranty is null & void
- All data has +/- 5% tolerance
- UL Listed
- Title 24 - JA8-2016 Strips: DRY rated, 2700K and above



SW24/6.0

STRIP: Static White



Compatible Extrusions

	SLIM	WIDE	ROND	TORQ	TRE3	LALO	TALO
DRY		✓	✓	✓	✓	✓	✓
DMP							
ENC							
WET							

	ARKA	TELA	VEEVE	FLUR	EMBD	LATO	MDIN	OPTI
DRY	✓	✓	✓	✓	✓	✓	✓	✓
DMP								
ENC								
WET								

Connector/Wire – In/Out

BW Bare Wire 24"	BRL Barrel 6"	CON6 Connector 6"	CON24 Connector 24"	CLS Not soldered
--------------------------------	-----------------------------	---------------------------------	-----------------------------------	--------------------------------

Compatible Power Supplies See website for additional power supply options

QZ 	iQ-PH-80 	QTM-DRIVE 	QTM-DC+CAP 	QTM-eLED
---------------	---------------------	----------------------	-----------------------	---------------------

Compatible Accessories

SNP-LEAD DRY only 22 - 20 AWG	SNP-INLINE DRY only 22 - 20 AWG	CLP-LEAD DRY only 22 - 18 AWG	CLP-INLINE DRY only 22 - 18 AWG	Q-mini-J
--	--	--	--	---------------------