

# CARDIFF TUNABLE WHITE

Indoor ADA Sconce



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

## GENERAL SPECIFICATION

**Tunable White:** LED option (TW) features tunable white technology that adjusts from 6500K-2700K. For proper control, fixture needs two 0-10V dimming controls.

**LED Tuning:** CCT tunable using 0-10V wall control. TRIAC, DALI, or DMX available upon request.

**LED Dimming:** Intensity adjustable using 1% 0-10V wall control. TRIAC, DALI, or DMX available upon request. Remote driver.


**Acrylic:** Acrylic is UL-94 HB Flame Class rated.

**Body:** Formed 18ga steel or .050 aluminum body. Optional painted white perforated top and bottom diffuser.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Custom:** Contact factory for custom lengths and lamping.

**Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:				
GL-4515-	TW1-	W-	NSN-	A
MODEL NO.	LAMPING	ACRYLIC	FINISH	OPTION(S)
<b>GL-4515</b> W in 6" mm 150 H in 18" mm 460 D in 4" mm 100	<b>TW1</b>	Standard: <b>W.</b> White Opal <b>S.</b> Satin White  Acrylic is UL-94 HB Flame Class rated.	Standard: Powder Coat <b>BLK</b> -Black <b>BL</b> -Blue <b>GR</b> -Gray <b>LG</b> -Light Gray <b>BE</b> -Beige <b>PAB</b> -Antique Brass <b>PA</b> -Painted Aluminum <b>PTC</b> -Painted Copper <b>WH</b> -White <b>DBZ</b> -Dark Bronze <b>NSN</b> -New Satin Nickel <b>BRN</b> -Brown <b>RD</b> -Red <b>CH</b> -Champagne <b>RG</b> -Reed Green <b>SG</b> -Sungold <b>GM</b> -Gun Metal <b>POR</b> -Oil Rubbed Bronze  Textured Powder <b>TLV</b> -Light Verdigris <b>TWH</b> -Textured White <b>TBL</b> -Textured Black <b>TS</b> -Textured Silver <b>TBN</b> -Terra Brown <b>TBZ</b> -Textured Bronze	<b>A.</b> No Options <b>EL.</b> Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage. <b>B.</b> Top Perforated Cover Painted white. <b>C.</b> BTM Perforated Cover Painted white.

All dimensions are nominal.

## Light Source Definition

Code	LED	CRI	Rated Life Hrs	Board Lumens	Board Kelvin
TW1	14W	+80	50000	1950	6500-2700

Universal Voltage unless otherwise specified.